

## Platinum series Ø22 mm control device accessories

## LED indicating modules (protected) clips onto LPX AU120 support

- Over voltage protection
- Protection against stray current in wiring
- Flickering phenomenon reduction
- Electrical life: 100.000 hours

type	colour	supply	description
<b>LED modules (steady light) (screw type)</b>			
LPX LPB3	green	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB4	red	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB5	yellow	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB6	blue	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB8	white	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPE*	*	85 - 140 VAC	LED integrated steady lamp module
LPX LPM3	green	185 - 265 VAC	LED integrated steady lamp module
LPX LPM4	red	185 - 265 VAC	LED integrated steady lamp module
LPX LPM5	yellow	185 - 265 VAC	LED integrated steady lamp module
LPX LPM6	blue	185 - 265 VAC	LED integrated steady lamp module
LPX LPM8	white	185 - 265 VAC	LED integrated steady lamp module

<b>LED modules (steady light) (push-in type)</b>			
LPX LPSB3	green	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPSB4	red	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPSB5	yellow	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPSB6	blue	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPSB8	white	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPSM3	green	185 - 265 VAC	LED integrated steady lamp module
LPX LPSM4	red	185 - 265 VAC	LED integrated steady lamp module
LPX LPSM5	yellow	185 - 265 VAC	LED integrated steady lamp module
LPX LPSM6	blue	185 - 265 VAC	LED integrated steady lamp module
LPX LPSM8	white	185 - 265 VAC	LED integrated steady lamp module

**Note:** Push-in technology for rigid cables or with ferrules (no screw driver required for insertion) guaranteed retaining force over time even in presence of vibration and/or impact.

<b>LED modules (flashing light) (screw type)</b>			
LPX LFB*	*	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFE*	*	85 - 140 VAC	LED integrated flashing lamp module
LPX LFM*	*	185 - 265 VAC	LED integrated flashing lamp module

\* Replace with: 3 (green) / 4 (red) / 5 (yellow) / 6 (blue) / 8 (white) - for colours

## Monoblock LED pilot lights Ø22 mm mounting

- Electrical life: >30.000 hours
- Protection degree: IP66, IP67 and IP69K
- Compliant with standards: IEC/EN 60947-1, IEC/EN60947-5-1, UL508, CSA C22.2 no 14

type	colour	supply voltage	IP rating	description
LPM LB1	orange	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB3	green	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB4	red	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB5	yellow	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB6	blue	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB7	t/parent	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM1	orange	230 VAC	66/67/69K	monoblock LED pilot light
LPM LM3	green	230 VAC	66/67/69K	monoblock LED pilot light
LPM LM4	red	230 VAC	66/67/69K	monoblock LED pilot light
LPM LM5	yellow	230 VAC	66/67/69K	monoblock LED pilot light
LPM LM6	blue	230 VAC	66/67/69K	monoblock LED pilot light
LPM LM7	t/parent	230 VAC	66/67/69K	monoblock LED pilot light

## Monoblock buzzer - continuous or pulse tone

LPC ZSA	black	9 - 15 VAC/DC	IP40	p/mount 90db/10 cm buzzer
LPC ZSB	black	18 - 30 VAC/DC	IP40	p/mount 90db/10 cm buzzer
LPC ZSM	black	185 - 265 VAC/DC	IP40	p/mount 90db/10 cm buzzer
LPC ZSAIP	black	9 - 15 VAC/DC	66/67/69K	p/mount 70db/10 cm buzzer
LPC ZSBIP	black	18 - 30 VAC/DC	66/67/69K	p/mount 70db/10 cm buzzer
LPC ZSMIP	black	185 - 265 VAC/DC	66/67/69K	p/mount 70db/10 cm buzzer

