

new



AD22-22MK02



AD22-22MR02



AD22-22VMG



AD22-22VAM...



AD30-30DSG22



AD30-30MR02



RZ3A1A60S3

**Panel mount control/indicating devices Ø22 mm**

type	colour	voltage ± 20%	mounting hole Ø	description
<b>Ø22 mm panel mount buzzer (IP40) Lens: Ø30 x 13 - Body: L 49 mm</b>				
• Continuous sound buzzer (80dB 10 cm)				
AD22-22MK02	black	24 VAC/DC	Ø22 mm	panel mount buzzer
AD22-22MK22	black	220 VAC	Ø22 mm	panel mount buzzer

**Combination buzzer/flashing LED pilot light**

• Intermittant sound and flashing pilot light				
AD22-22MR02	red	24 VAC/DC	Ø22 mm	self-flash LED p/light + buzzer
AD22-22MR22	red	220 VAC	Ø22 mm	self-flash LED p/light + buzzer

**Ø22 mm panel mount volt/amp/Hz indicators (IP63) Lens: Ø30 x 15 mm - Body: L 31 mm**

AC voltmeter	20 - 500 VAC			
AD22-22VMR	red	20 - 500 VAC	Ø22 mm	voltmeter panel indicator light
AD22-22VMG	green	20 - 500 VAC	Ø22 mm	voltmeter panel indicator light
AD22-22VMY	yellow	20 - 500 VAC	Ø22 mm	voltmeter panel indicator light
AD22-22VMB	blue	20 - 500 VAC	Ø22 mm	voltmeter panel indicator light
AD22-22VMW	white	20 - 500 VAC	Ø22 mm	voltmeter panel indicator light
DC voltmeter	5 - 60 VDC			
AD22-22VBR	red	5 - 60 VDC	Ø22 mm	voltmeter panel indicator light
AD22-22VBG	green	5 - 60 VDC	Ø22 mm	voltmeter panel indicator light
AD22-22VBY	yellow	5 - 60 VDC	Ø22 mm	voltmeter panel indicator light
AD22-22VBB	blue	5 - 60 VDC	Ø22 mm	voltmeter panel indicator light
AD22-22VBW	white	5 - 60 VDC	Ø22 mm	voltmeter panel indicator light

AC ammeter	0 - 100A (with Current Transformer)			
AD22-22AM*	*	0 - 100A	Ø22 mm	ammeter panel indicator light

**Combination AC volt/ammeter 20 - 500 VAC / 0 - 100A AC (with Current Transformer)**

AD22-22VAM*	*	20-500 / 0-100A	Ø22 mm	volt/ammeter panel indicator light
-------------	---	-----------------	--------	------------------------------------

\* Add: R (red) / G (green) / Y (yellow) / B (blue) W (white) - for colour

**Ø30 mm LED pilot lights (high brightness) (IP63) Lens: Ø36.2 x 15 - Body: L 40 mm**

AD30-30DSR02	red	24 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSG02	green	24 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSY02	yellow	24 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSB02	blue	24 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSW02	white	24 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSR22	red	220 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSG22	green	220 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSY22	yellow	220 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSB22	blue	220 VAC/DC	Ø30 mm	panel mount LED pilot light
AD30-30DSR38	red	380 VAC	Ø30 mm	panel mount LED pilot light
AD30-30DSG38	green	380 VAC	Ø30 mm	panel mount LED pilot light
AD30-30DSY38	yellow	380 VAC	Ø30 mm	panel mount LED pilot light
AD30-30DSB38	blue	380 VAC	Ø30 mm	panel mount LED pilot light
AD30-30DSW38	white	380 VAC	Ø30 mm	panel mount LED pilot light

**Ø30 mm panel mount buzzer (IP40) Lens: Ø36.2 x 15 - Body: L 40 mm**

Combination buzzer/flashing LED pilot light				
• Intermittant sound and flashing				
AD30-30MR02	red	24 VAC/DC	Ø30 mm	self-flash LED p/light + buzzer
AD30-30MR22	red	220 VAC/DC	Ø30 mm	self-flash LED p/light + buzzer

**Panel mount electronic timer Ø22 mm (IP65)**

Function:	On-Delay timer	Range:	0 - 60 seconds	
Mounting:	Mounts through standard Ø22.5 mm pushbutton hole			
Supply Voltage:	24 VDC			
Switching current:	200 mA			
Indication:	Facia illuminates - green during timing / red - at time lapse			
Operating temp:	-5 - +55°C			
RZ3A1A60S3	0 - 60 sec	10 - 30 VDC	Ø22 mm	on-delay panel mount analog timer