



KN3C-1R021

new



KN3C-R1221



MTS-102



DS-12



AD22-POT05K



SB7-CA45R



SDL-012Y

Toggle switches

type	current lth	pos.	config	mount hole Ø	switch	description	
------	-------------	------	--------	--------------	--------	-------------	--

KN3C series - Standard toggle switches

- Rating: 20A 125 VAC / 15A 250 VAC
- Termination: 6.3 mm tab terminals
(accepts 6.3 mm std power toggle switch *m* push-on lugs)
- Mounting: **M12** x P1.0 mm threaded collar (mounts through Ø12.2 mm panel hole)
- Dielectric strength: 1500 VAC (1 minute)
- Legend: Supplied with ON/OFF legend plate

Single pole toggle switches

KN3C-R1021	15A	2 pos	on-off	12.7 mm	SPST	std power toggle switch	
KN3C-R1121	15A	2 pos	on-on	12.7 mm	SPDT	std power toggle switch	
KN3C-R1122	15A	3 pos	on-off-on	12.7 mm	SPDT	std power toggle switch	

Double pole toggle switches

KN3C-R1221	15A	2 pos	on-off	12.7 mm	DPST	std power toggle switch	
KN3C-R1321	15A	2 pos	on-on	12.7 mm	DPDT	std power toggle switch	
KN3C-R1322	15A	3 pos	on-off-on	12.7 mm	DPDT	std power toggle switch	

Accessories - for above toggle switches

WP-02	boot	rubber protection boot M12 for KN3C toggle switches					
-------	------	---	--	--	--	--	--

MTS series - Miniature toggle switches

- Rating: 6A 125 VAC / 3A 250 VAC
- Termination: Solder terminals (W) 2.05 mm
- Mounting: **M6** x 0.75 threaded collar (mounts through Ø6 mm panel hole)
- Dielectric strength: 1000 VAC (1 minute)
- Operating temp: -25 to +85°C

Single pole miniature toggle switches

MTS-102	3A	2 pos	on-on	6.5 mm	SPDT	miniature toggle switch	
MTS-102T	3A	2 pos	on-(on)	6.5 mm	SPDT	spring return from R	
MTS-103	3A	3 pos	on-off-on	6.5 mm	SPDT	centre off	
MTS-103D	3A	3 pos	(on)-off-(on)	6.5 mm	SPDT	spring return from L+R	
MTS-103T	3A	3 pos	on-off-(on)	6.5 mm	SPDT	spring return from R	

Double pole miniature toggle switches

MTS-202	3A	2 pos	on-on	6.5 mm	SPDT	miniature toggle switch	
MTS-203	3A	3 pos	on-off-on	6.5 mm	SPDT	centre off	

Miniature pushbutton switch - black button

DS-12	3A	2 pos	on-(on)	6.5 mm	SPDT	spring return (<i>blk</i> button)	
-------	----	-------	---------	--------	------	------------------------------------	--

Accessories - for above miniature switches

WP-01	boot	rubber protection boot for MTS miniature toggle switch					
-------	------	---	--	--	--	--	--

Panel mount potentiometer Ø22 mm (IP65)

Potentiometer - (1 turn)

AD22-POT01K	black	–	0 - 1kΩ	Ø22 mm	–	panel mnt potentiometer	
AD22-POT05K	black	–	0 - 5kΩ	Ø22 mm	–	panel mnt potentiometer	

Econo one-piece pushbuttons Ø22 mm (IP40)

type	colour	contact	mounting hole Ø	description	
------	--------	---------	-----------------	-------------	--

SB7-CA45R	red	1NO+1NC	Ø22 mm	one-piece flush pushbutton	
SB7-CA35G	green	1NO+1NC	Ø22 mm	one-piece flush pushbutton	
SB7-CA25B	black	1NO+1NC	Ø22 mm	one-piece flush pushbutton	
SB7-CD25B	black	1NO+1NC	Ø22 mm	two position selector switch	

Neon indicating pilot lights Ø10 mm (IP65) 6.3 mm push-on tab terminals

		voltage		
SDL-012R	red	230 VAC	Ø10 mm	panel mount neon indicator light
SDL-012G	green	230 VAC	Ø10 mm	panel mount neon indicator light
SDL-012Y	yellow	230 VAC	Ø10 mm	panel mount neon indicator light

For "push-on" female disconnect terminals for above **SDL / GQ** series (metallic pilot light- see page **D-28**) – see page **L-20**