



### Signal beacons Ø62 mm

Signal beacons are fundamental elements for visual and audible signalling of system status in manufacturing processes.

- IP30 with base
- IP54 without base
- Bases for various mounting solutions are supplied separately

type	colour	voltage	description
------	--------	---------	-------------

#### Steady light modules BA15d fitting, direct supply (lamp not included) Ø62 mm

**LB6EL\*** \* 24V AC/DC or 230VAC direct supply steady light module

#### Blinking or steady light modules BA15d fitting (lamp not supplied)

**LB6GLB\*** \* 12 - 48 VAC/DC blinking light module (no lamp)

**LB6GLM\*** \* 24 - 230 VAC blinking light module (no lamp)

\* Replace with: 1= orange / 3= green / 4= red / 5= yellow / 6= blue / 8= white

#### Bases for above signal beacons

**LB6BP03** horizontal surface mount base

**LB6BP05** through hole mounting Ø22 mm with locknut

**LB6BP07** for extended tube connection

### Signal towers Ø70 mm (IP65)

Signal towers can be assembled by stacking up to seven modules of:

1. Up to 7 light modules (steady or blinking) less one, if a sound module is required
2. Add connection module for terminating
3. Add mounting accessories if required

- Light modules: steady light / blinking light
- Sound modules: continuous or pulsed sound

#### Steady light modules standard BA15d lamp filament or LED (not included)

**LT7EL\*** \* 12 - 260 VAC/DC steady light stackable module

#### Blinking light modules standard BA15d lamp filament or LED (not included)

**LT7GLB\*** \* 24 VAC/DC blinking light module (no lamp)

**LT7GLM\*** \* 230 VAC blinking light module (no lamp)

\* Replace with: 1= orange / 3= green / 4= red / 5= yellow / 6= blue / 8= white

#### Sound modules (pulsed or continuous)

**LT7S2B** - 24 VAC/DC pulsed or continuous IP65

**LT7S2M** - 230 VAC pulsed or continuous IP65

#### Connection modules (complete with cover)

**LT7CP01** black bottom entry connection module (for plastic tubes)

#### Accessories for beacons and signal towers (above)

**LT7BP01** horizontal surface mount base with tube extension

**LT7BP02** vertical wall mount base with tube extension

**LT7TP0100** 100 mm extension tube for base (stackable sections)

### Super bright LED signal lamps BA15d (360° illumination) up to 25 000 hours

type	colour	voltage	description
<b>LT7ALLB4</b>	red	24 VAC/DC	BA15d LED lamp for towers
<b>LT7ALLB3</b>	green	24 VAC/DC	BA15d LED lamp for towers
<b>LT7ALLB5</b>	amber	24 VAC/DC	BA15d LED lamp for towers
<b>LT7ALLB6</b>	blue	24 VAC/DC	BA15d LED lamp for towers
<b>LT7ALLB8</b>	white	24 VAC/DC	BA15d LED lamp for towers
<b>LT7ALLM4</b>	red	230 VAC	BA15d LED lamp for towers
<b>LT7ALLM3</b>	green	230 VAC	BA15d LED lamp for towers
<b>LT7ALLM5</b>	amber	230 VAC	BA15d LED lamp for towers
<b>LT7ALLM6</b>	blue	230 VAC	BA15d LED lamp for towers
<b>LT7ALLM8</b>	white	230 VAC	BA15d LED lamp for towers