



38603



38654



38802



90063

**LED luminous devices engineered for industrial applications and machinery**

type	lens colour	dB @ 1m max	supply voltage	description	dimensions (mm)	
					Ø	ext.

**MICROLAMP LED - Multifunctional LED signalling beacon (IP54)**

- Multi-voltage: 12/24 VAC/DC (or) 90 - 240 VAC
- 2 light effects: Steady - flashing (*selectable via terminals*)
- Surface mount **M16** cable gland entry (*excluding gland*)

<b>38602</b>	amber	-	12 - 24 VAC/DC	surface mnt signalling device	86	90
<b>38603</b>	red	-	12 - 24 VAC/DC	surface mnt signalling device	86	90
<b>38604</b>	green	-	12 - 24 VAC/DC	surface mnt signalling device	86	90
<b>38622</b>	amber	-	90 - 240 VAC	surface mnt signalling device	86	90
<b>38623</b>	red	-	90 - 240 VAC	surface mnt signalling device	86	90
<b>38624</b>	green	-	90 - 240 VAC	surface mnt signalling device	86	90

**MICROLAMP LED and ACOUSTIC - LED signalling beacon (IP30)**

- 2 alarm levels: Continuous sound with steady light (or) intermittent sound with flashing light

<b>38632</b>	amber	72	12 - 24 VAC/DC	surface mnt signalling device	86	111
<b>38633</b>	red	72	12 - 24 VAC/DC	surface mnt signalling device	86	111
<b>38634</b>	green	72	12 - 24 VAC/DC	surface mnt signalling device	86	111
<b>38652</b>	amber	72	90 - 240 VAC	surface mnt signalling device	86	111
<b>38653</b>	red	72	90 - 240 VAC	surface mnt signalling device	86	111
<b>38654</b>	green	72	90 - 240 VAC	surface mnt signalling device	86	111

*Other colours available on request.*

**OVOLUX LED - Multifunctional LED signalling beacon (IP65)**

- Multi-voltage: 12/24 VAC/DC (or) 90 - 240 VAC
- 4 light effects: Steady - single flash - double flash - triple flash (*selectable via dip-switches*)
- "M" version surface mount **M16** cable gland entry (*gland supplied*)
- Bright LED with maximised performance (*CDmax 35*)

<b>38802</b>	amber	-	12 - 24 VAC/DC	panel mount signalling device	76	69
<b>38803</b>	red	-	12 - 24 VAC/DC	panel mount signalling device	76	69
<b>38812</b>	amber	-	90 - 240 VAC	panel mount signalling device	76	69
<b>38813</b>	red	-	90 - 240 VAC	panel mount signalling device	76	69

*Other colours available on request.*

**ROTALLARM S LED - Multifunctional rotating beacon (IP65)**

**ROTALLARM LED** features a powerful multi-voltage and multifunction SMD LED electronic circuit offering outstanding performances together with the highest life expectancy in todays market. The structure guarantees high impact and vibration resistance as well as a high IP grade

- 3 light effects - **Steady light**  
**Flashing**  
**Rotating** (*simulates traditional rotating beacon*)

- 32 x 5050 Bright LEDs for improved visibility
- PC/ABS base with self-extinguishing polycarbonate dome
- Base mount **M20** cable gland entry (*gland supplied*)

**Rotallarm LED rotating beacons (H) 212 x Ø142 mm**

<b>90061</b>	blue	-	12 - 24 VAC/DC	multifunctional LED beacon	142	212
<b>90062</b>	amber	-	12 - 24 VAC/DC	multifunctional LED beacon	142	212
<b>90063</b>	red	-	12 - 24 VAC/DC	multifunctional LED beacon	142	212
<b>90064</b>	green	-	12 - 24 VAC/DC	multifunctional LED beacon	142	212
<b>90081</b>	blue	-	90 - 240 VAC	multifunctional LED beacon	142	212
<b>90082</b>	amber	-	90 - 240 VAC	multifunctional LED beacon	142	212
<b>90083</b>	red	-	90 - 240 VAC	multifunctional LED beacon	142	212
<b>90084</b>	green	-	90 - 240 VAC	multifunctional LED beacon	142	212

**72692** grey - wall mounting bracket for above Rotallarm beacon