



**GST multipole connectors**

Rated voltage: 250V      Rated current: 16A  
 Protection degree: IP20      Colour: White (black available on request)

• Quick, easy and reliable connection technology with Integrated locking device

| type | current (A) | No. poles | for cable (Ø mm) | wire (mm <sup>2</sup> ) | description | panel hole Ø |
|------|-------------|-----------|------------------|-------------------------|-------------|--------------|
|------|-------------|-----------|------------------|-------------------------|-------------|--------------|

**GST 15i3 (Gesis mini) connectors 16A/250V**

| In-line connectors (with strain relief) |     | screw connection |           |           |                               |
|---|-----|------------------|-----------|-----------|-------------------------------|
| 91.921.3053.0                           | 16A | 2 pole           | 5.5 - 8.5 | 0.5 - 1.5 | female in-line connector      |
| 91.922.3053.0                           | 16A | 2 pole           | 5.5 - 8.5 | 0.5 - 1.5 | male in-line connector        |
| 91.931.3053.0                           | 16A | 3 pole           | 5.5 - 8.5 | 0.5 - 1.5 | female in-line connector      |
| 91.932.3053.0                           | 16A | 3 pole           | 5.5 - 8.5 | 0.5 - 1.5 | male in-line connector        |
| 91.931.9053.0                           | 16A | 3 pole           | –         | 0.5 - 1.5 | flush female p/mnt connector  |
| 91.931.9153.0                           | 16A | 3 pole           | –         | 0.5 - 1.6 | protruding female p/mnt conn. |
| 91.932.9053.0                           | 16A | 3 pole           | –         | 0.5 - 1.5 | flush male p/mnt connector    |
| 91.932.9153.0                           | 16A | 3 pole           | –         | 0.5 - 1.6 | protruding male p/mnt conn.   |

**GST 18i3 (Gesis) connectors 16A/250V**

| In-line connectors (with strain relief) |     | screw connection |            |            |                          |
|---|-----|------------------|------------|------------|--------------------------|
| 92.931.3053.0                           | 16A | 3 pole           | 6.5 - 10.5 | 0.75 - 2.5 | female in-line connector |
| 92.932.3053.0                           | 16A | 3 pole           | 6.5 - 10.5 | 0.75 - 2.5 | male in-line connector   |

**Panel mounting (snap-in) spring-loaded screwless connection**

|               |     |        |   |            |                              |
|---------------|-----|--------|---|------------|------------------------------|
| 92.031.9658.0 | 16A | 3 pole | – | 0.75 - 2.5 | female panel mount connector |
| 92.032.9658.0 | 16A | 3 pole | – | 0.75 - 2.5 | male panel mount connector   |

**Accessories for GST connectors**

|               |       |        |  |  |  |
|---------------|-------|--------|--|--|--|
| 91.030.6053.0 | 16A   | 3 pole |  |  | 1 in / 2 out distribution unit for GST15i connectors |
| 91.030.4953.0 | 16A   | 3 pole |  |  | 1 in / 3 out distribution unit for GST15i connectors |
| 91.030.5853.0 | 16A   | 3 pole |  |  | U-type intermediate coupling for GST 15i connectors  |
| 91.030.5953.0 | 16A   | 3 pole |  |  | in-line intermediate coupling for GST 15i connectors |
| 92.030.4853.0 | 16A   | 3 pole |  |  | 1 in / 3 out distribution unit for GST18i connectors |
| 92.030.5958.0 | 16A   | 3 pole |  |  | in-line intermediate coupling for GST 18i connectors |
| 05.587.3156.0 | lock  | –      |  |  | locking device for in-line connectors                |
| 05.561.3653.0 | cover | –      |  |  | protection cover for GST18i female connectors        |

**Revos MINI - industrial multipole connectors**

Protection degree: IP 65 (when used with appropriate cable gland)

| type | current (A) | No. poles | rated voltage | connect type | cable inlet | description |
|------|-------------|-----------|---------------|--------------|-------------|-------------|
|------|-------------|-----------|---------------|--------------|-------------|-------------|

• Set is made up with - contact inserts (male and female) - base - hood

**Revos MINI 10A/400V**

| Contact inserts |     | Screw connection - (cables 0.5 - 2.5 mm <sup>2</sup> ) |       |       |   |                                |
|-----------------|-----|--|-------|-------|---|--------------------------------|
| 73.310.0353.0   | 10A | 3p + ⊥   | 400 V | screw | – | male insert - screw terminal   |
| 73.310.0453.0   | 10A | 4p + ⊥   | 400 V | screw | – | male insert - screw terminal   |
| 73.300.0353.0   | 10A | 3p + ⊥   | 400 V | screw | – | female insert - screw terminal |
| 73.300.0453.0   | 10A | 4p + ⊥   | 400 V | screw | – | female insert - screw terminal |

**Crimp connection - (crimp contacts to be ordered separately)**

|               |     |        |       |       |                           |                                |
|---------------|-----|--------|-------|-------|---------------------------|--------------------------------|
| 73.710.0753.0 | 10A | 7p + ⊥ | 250 V | crimp | –                         | male insert - for crimp pins   |
| 73.710.0853.0 | 10A | 8 pole | 50 V  | crimp | –                         | male insert - for crimp pins   |
| 05.544.1029.0 | 10A | –      | 250 V | crimp | .75 - 1.5 mm <sup>2</sup> | male crimp contact pins        |
| 73.700.0753.0 | 10A | 7p + ⊥ | 250 V | crimp | –                         | female insert - for crimp pins |
| 73.700.0853.0 | 10A | 8 pole | 50 V  | crimp | –                         | female insert - for crimp pins |
| 02.124.1029.0 | 10A | –      | 250 V | crimp | .75 - 1.5 mm <sup>2</sup> | female crimp contact pins      |

**Bases with locking lever for hood connection**

|               |         |         |  |      |          |                               |
|---------------|---------|---------|--|------|----------|-------------------------------|
| 76.320.0729.0 | metal   | 3/4/7/8 |  | open | straight | base for contact inserts      |
| 76.321.0729.0 | metal   | 3/4/7/8 |  | open | 90°      | angled base for cont. inserts |
| 76.320.0753.0 | plastic | 3/4/7/8 |  | open | straight | base for contact inserts      |
| 76.321.0753.0 | plastic | 3/4/7/8 |  | open | 90°      | angled base for cont. inserts |

**Hoods with threaded collar to accept M20 cable glands**

|               |         |         |  |     |          |                               |
|---------------|---------|---------|--|-----|----------|-------------------------------|
| 76.352.0736.1 | metal   | 3/4/7/8 |  | M20 | straight | hood for contact inserts      |
| 76.350.0736.1 | metal   | 3/4/7/8 |  | M20 | 90°      | angled hood for cont. inserts |
| 76.352.0760.1 | plastic | 3/4/7/8 |  | M20 | straight | hood for contact inserts      |
| 76.350.0760.1 | plastic | 3/4/7/8 |  | M20 | 90°      | angled hood for cont. inserts |