



143017



143018



143119



106300



106538

MULTIBLOC series - NH-fuse switch disconnecter (for panel mounting)

- Parking position of the switch cover (even with inserted fuse-links)
- Modular terminal covers can be extended as required
- Lid lock and lid seal (with optional accessories)

Utilization category to IEC/EN 60947-3	00	1
--	----	---

Ue: AC 400V; Ie =	160A	250A	AC 23 B
Ue: AC 500V; Ie =	160A	250A	AC 22 B
Ue: AC 690V; Ie =	125A	200A	AC 21 B
Ue: DC 220V; Ie =	160A	250A	DC 22 B

type	No. poles	fuse size	max. current	cable terminal	description	dimensions (mm) (H) (W) (D)		
------	-----------	-----------	--------------	----------------	-------------	--------------------------------	--	--

NH - Fuse switch disconnecter (panel mounting) IP30

- Rated operational voltage: 690 V
- Rated impulse withstand Uimp: 8 kV
- Insulation voltage Ui: 1000 V

NH00 - Fuse switch disconnecter

143017	1	00	160A	M8	fuse switch disconnecter	184	42	84
143018	2	00	160A	M8	fuse switch disconnecter	184	84	84

NH1 - Fuse switch disconnecter

143119	1	1	250A	M10	fuse switch disconnecter	184	71	84
143118	2	1	250A	M10	fuse switch disconnecter	184	142	84

Accessories for above switch disconnectors

140149	1/2	00	cable termination cover for NH00 switches				(2 pcs)	
140354	1/2	1	cable termination cover for NH1 switches				(2 pcs)	
140155	1/2	00/1	cover sealing set for switch disconnecter				sizes 00 & 1	
140852	1/2		monitoring switch for door position status				all sizes	

60 mm busbar system

Busbar supports for busbars (W) 12 - 30 mm x (D) 5/10 mm

106300	3	busbar support for 12 - 30 mm x 5/10 mm bars		185	17	43
106302*	1	busbar support for 12 - 30 mm x 5/10 mm bars		77	17	43

* 1 pole unit can be attached to each other for two pole or a 3 pole to make a 4 pole support

Busbar 3 phase feed-in terminals

106096	3	bar mount feed-in terminal	16...50 mm ²	201	54	44
106097	3	bar mount feed-in terminal	16...70 mm ²	201	108	80
106098	3	bar mount feed-in terminal	16...185 mm ²	201	108	80

Component adaptors for direct mounting on 60 mm system busbars

106521	3	25A	1 rail	4 mm ²	component adaptor	207	45
106523	3	25A	2 rails	4 mm ²	component adaptor	260	45
106526	3	32A	1 rail	6 mm ²	component adaptor	207	54
106528	3	32A	2 rails	6 mm ²	component adaptor	260	54
106530	3	32A	1 rail	6 mm ²	component adaptor	207	72
106531	3	32A	2 rails	6 mm ²	component adaptor	260	72
106533	3	63A	1 rail	10 mm ²	component adaptor	207	54
106535	3	63A	2 rails	10 mm ²	component adaptor	260	54
106537	3	63A	1 rail	10 mm ²	component adaptor	207	72
106538	3	63A	2 rails	10 mm ²	component adaptor	260	72
106539	3	63A	2 rails	10 mm ²	component adaptor	207	81
106544	3	80A	2 rails	16 mm ²	component adaptor	260	72

Protection cover for 60 mm system

126074	3	bar mounted cover support bracket				
126075	3	panel front cover protection 1000 mm				2met

Busbar support for 100 and 185 mm system

188100	3	100 mm	busbar support for 30 - 60 mm x 10 mm bars	324	28	50
188101	3	185 mm	busbar support for 30 - 120 mm x 10 mm bars	573	28	50
188102	1	100/185	busbar support for 30 - 120 mm x 10 mm bars	224	25	50