



Distribution terminals(DIN rail mountable) - 7, 11, 15 way

Maximum operating temperature: -5...+85°C (heat resistance to +130°C)
 Insert material: Brass with zinc plated screws
 Insulating body material: Support material polyamide – cover polycarbonate
 Mounting: DIN rail mounting (EN50022) or screw down
 Standards: EN 60998-1, EN 60998-2-1

type	No. ways	description	max. wire size (mm ²)				dimensions (mm)		
			input	10	16	25	35	(H)	(W)

Multi way terminal posts 750V

M107V	7	green (earth) bar	2x16	5x	-	-	-	59	19	34
M1011V	11	green (earth) bar	2x16	9x	-	-	-	88	19	34
M1015V	15	green (earth) bar	2x16	13x	-	-	-	114	19	34
M107B	7	blue (neutral) bar	2x16	5x	-	-	-	59	19	34
M1011B	11	blue (neutral) bar	2x16	9x	-	-	-	88	19	34
M1015B	15	blue (neutral) bar	2x16	13x	-	-	-	114	19	34
M107G	7	grey (phase) bar	2x16	5x	-	-	-	59	19	34
M1011G	11	grey (phase) bar	2x16	9x	-	-	-	88	19	34
M1015G	15	grey (phase) bar	2x16	13x	-	-	-	114	19	34

Multi-pole protected distribution terminals (DIN rail mountable) 750V

1MR series - Distribution terminals

- DIN rail or chassis mounting
- Low profile 45 mm deep (*height of standard MCBs*)
- Supplied with insulated DIN rail cover
- Rated voltage: 750V

type	No ways	amps	no. bars	max. wire size (mm ²)				dimensions (mm)		
				input	10	16	25	35	(H)	(W)

2 pole - (1Ph+N)

l_{pk} 12kA - l_{cc rms} 6kA - l_{cw rms} (1s) 1.9kA

1MR6372	7	63A	2	2x16	5x	-	-	-	68	59	45
1MR63112	11	63A	2	2x16	9x	-	-	-	68	88	45

l_{pk} 22kA - l_{cc rms} 11kA - l_{cw rms} (1s) 6kA

1MR12572	7	125A	2	35 mm ²	5x	-	1x	-	47	68	45
1MR125112	11	125A	2	35 mm ²	6x	2x	2x	-	47	105	45
1MR125152	15	125A	2	35 mm ²	10x	2x	2x	-	47	134	45

4 pole - (3ph+N)

l_{pk} 22kA - l_{cc rms} 11kA - l_{cw rms} (1s) 6kA

1MR12574	7	125A	4	35 mm ²	5x	-	1x	-	98	72	45
1MR125114	11	125A	4	35 mm ²	6x	2x	2x	-	98	109	45
1MR125154	15	125A	4	35 mm ²	10x	2x	2x	-	98	138	45

Additional terminal bars M107/1011/1015 can easily be clipped onto above distribution terminals

160A stepped distribution block 70 mm deep profile

l_{pk} 24kA - l_{cc rms} 12kA - l_{cw rms} (1s) 8kA

1MR160134	13	160A	4	50 mm ²	-	8x	2x	2x	136	186	70
------------------	----	------	---	--------------------	---	----	----	----	-----	-----	----

3MR series - Distribution terminal

Separated incoming terminals (two extra large incoming phase terminals on either side)

l_{pk} 22kA - l_{cc rms} 11kA - l_{cw rms} (1s) 6kA

3MR125164	16	125A	4	35 mm ²	11x	2x	2x	-	107	202	45
------------------	----	------	---	--------------------	-----	----	----	---	-----	-----	----

l_{pk} 24kA - l_{cc rms} 12kA - l_{cw rms} (1s) 8kA

3MR160164	16	160A	4	50 mm ²	11x	-	2x	2x	107	233	45
------------------	----	------	---	--------------------	-----	---	----	----	-----	-----	----