



Slotted trunking

Ezi Canal slotted cable ducting features an improved cover design for ease of opening and closing, permitting easy access to wiring in control panels. Meets maximum wire capacity requirements and space constraints (*from small control panels to large integrated systems*) to provide effective support for demanding wire management solutions.

Manufactured from high-impact, self-extinguishing, warp-proof rigid PVC material providing a shock proof insulated protection solution resistant to acids, oils and grease. Used for general purpose control panel wiring to provide improved aesthetics and a neater wire management solution in high density control panels.

- Simple open/close cover design for easy access to wiring in control panel
- Double score-line permits finger/slot or complete sidewall removal
- Coining process for burr-free edges to protect hands and wiring from abrasion
- Restricted slot design retains wire within slot for fast, easy wire installation or removal
- Duct and cover form a flush sidewall to provide increased capacity and improved appearance
- UL94 flammability rating V-0 for excellent flame retardation

Standard colour: Grey - others available on request (*volume dependant*)
 Standard length: Supplied in two meter lengths, complete with covers

type	dimensions (mm)		colour	description	slot A (mm)	finger B (mm)	carton qty (L - 2 m)
	(W)	(H)					

Narrow slotted trunking Finger: 6 mm / Slot - 4 mm (*10 mm pitch*)

• Narrow slot/finger design to closely fit spacing of high density terminal blocks and I/O modules

KKC1518	15	18	grey	PVC slotted cable trunking	5	7.5	112
TSL025025N	25	25	grey	PVC slotted cable trunking	4	6	48
TSL025040N	25	40	grey	PVC slotted cable trunking	4	6	40
TSL040040N	40	40	grey	PVC slotted cable trunking	4	6	24
TSL060040N	60	40	grey	PVC slotted cable trunking	4	6	24
TSL080040N	80	40	grey	PVC slotted cable trunking	4	6	18
TSL025060N	25	60	grey	PVC slotted cable trunking	4	6	30
TSL040060N	40	60	grey	PVC slotted cable trunking	4	6	28
TSL060060N	60	60	grey	PVC slotted cable trunking	4	6	18
TSL080060N	80	60	grey	PVC slotted cable trunking	4	6	14
TSL100060N	100	60	grey	PVC slotted cable trunking	4	6	12
TSL025080N	25	80	grey	PVC slotted cable trunking	4	6	28
TSL040080N	40	80	grey	PVC slotted cable trunking	4	6	20
TSL060080N	60	80	grey	PVC slotted cable trunking	4	6	12
TSL080080N	80	80	grey	PVC slotted cable trunking	4	6	8
TSL100080N	100	80	grey	PVC slotted cable trunking	4	6	8
TSL040100N	40	100	grey	PVC slotted cable trunking	4	6	16
TSL060100N	60	100	grey	PVC slotted cable trunking	4	6	12
TSL080100N	80	100	grey	PVC slotted cable trunking	4	6	8
TSL100100N	100	100	grey	PVC slotted cable trunking	4	6	8

Wide slotted trunking Finger: 12 mm / Slot - 8 mm (*20 mm pitch*)

TSL040060W	40	60	grey	PVC slotted cable trunking	8	12	28
TSL060060W	60	60	grey	PVC slotted cable trunking	8	12	18
TSL080060W	80	60	grey	PVC slotted cable trunking	8	12	14
TSL100060W	100	60	grey	PVC slotted cable trunking	8	12	12
TSL040080W	40	80	grey	PVC slotted cable trunking	8	12	20
TSL060080W	60	80	grey	PVC slotted cable trunking	8	12	12
TSL080080W	80	80	grey	PVC slotted cable trunking	8	12	8
TSL100080W	100	80	grey	PVC slotted cable trunking	8	12	8
TSL040100W	40	100	grey	PVC slotted cable trunking	8	12	16
TSL060100W	60	100	grey	PVC slotted cable trunking	8	12	12
TSL080100W	80	100	grey	PVC slotted cable trunking	8	12	8
TSL100100W	100	100	grey	PVC slotted cable trunking	8	12	8

Note: 10% off list price for full carton quantities of **TSL** trunking (above) - add /B to end of part number (e.g **TSL025040N/B**)

Spare covers for above trunking

TSM025	25	-	grey	spare PVC trunking covers	-	-	80
TSM040	40	-	grey	spare PVC trunking covers	-	-	80
TSM060	60	-	grey	spare PVC trunking covers	-	-	80
TSM080	80	-	grey	spare PVC trunking covers	-	-	80
TSM100	100	-	grey	spare PVC trunking covers	-	-	68

Trunking accessories

553415	84	14	grey	sectionable cable retainer clip			(10 pcs)
---------------	----	----	------	---------------------------------	--	--	----------

For **VTC125** - wiring duct cutter, see page (L-13)