

Platinum series Ø22 mm control device accessories

LED indicating modules (protected) clips onto LPX AU120 support

- Overvoltage protection
- Protection against stray current in wiring
- Flickering phenomenon reduction
- Electrical life: 100.000 hours

type	colour	supply	description
LED module (steady light)			
LPX LPB3	green	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB4	red	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB5	yellow	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB6	blue	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPB8	white	12 - 30 VAC/DC	LED integrated steady lamp module
LPX LPE*	*	85 - 140 VAC	LED integrated steady lamp module
LPX LPM3	green	185 - 265 VAC	LED integrated steady lamp module
LPX LPM4	red	185 - 265 VAC	LED integrated steady lamp module
LPX LPM5	yellow	185 - 265 VAC	LED integrated steady lamp module
LPX LPM6	blue	185 - 265 VAC	LED integrated steady lamp module
LPX LPM8	white	185 - 265 VAC	LED integrated steady lamp module

LED module (blinking light)

LPX LFB3	green	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFB4	red	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFB5	yellow	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFB6	blue	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFB8	white	12 - 30 VAC/DC	LED integrated flashing lamp module
LPX LFE*	*	85 - 140 VAC	LED integrated flashing lamp module
LPX LFM3	green	185 - 265 VAC	LED integrated flashing module
LPX LFM4	red	185 - 265 VAC	LED integrated flashing module
LPX LFM5	yellow	185 - 265 VAC	LED integrated flashing module
LPX LFM6	blue	185 - 265 VAC	LED integrated flashing module
LPX LFM8	white	185 - 265 VAC	LED integrated flashing module

* Add: 3 (green) / 4 (red) / 5 (yellow) / 6 (blue) / 8 (white) - for colours

LED module support

LPX AU120	LED module support for illuminated heads
-----------	--

Monoblock LED pilot lights Ø22 mm mounting

- Protection degree: IP66, IP67 and IP69K
- Electrical life: >30.000 hours
- Compliant with standards: IEC/EN 60947-1, IEC/EN60947-5-1, UL508, CSA C22.2 no 14

type	colour	supply voltage	IP rating	description
LPM LB3	green	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB4	red	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB5	yellow	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB6	blue	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LB7	t/parent	24 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM3	green	230 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM4	red	230 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM5	yellow	230 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM6	blue	230 VAC/DC	66/67/69K	monoblock LED pilot light
LPM LM7	t/parent	230 VAC/DC	66/67/69K	monoblock LED pilot light

Monoblock buzzer - continuous or pulse tone

LPCZSA	black	9 - 15 VAC/DC	IP40	90db/10cm monoblock buzzer
LPCZSB	black	18 - 30 VAC/DC	IP40	90db/10cm monoblock buzzer
LPCZSM	black	185 - 265 VAC/DC	IP40	90db/10cm monoblock buzzer
LPCZSAIP	black	9 - 15 VAC/DC	66/67/69K	70db/10cm monoblock buzzer
LPCZSBIP	black	18 - 30 VAC/DC	66/67/69K	70db/10cm monoblock buzzer
LPCZSMIP	black	185 - 265 VAC/DC	66/67/69K	70db/10cm monoblock buzzer



LPX LP...



LPX LF...



LPX A130



LPX AU120



LPM LB3



LPM LB5



LPCZSA

new