




42200



42001



42021



50415



50424

Industrial motor driven sirens

type	supply voltage	dB @ 1m	description	IP	run duration		dimensions	
					on	off	(Ø)	(H)

MICRO W10 series motor driven sirens

Ideal choice for industrial applications, from general-purpose signalization to warning.

- Can be installed vertically or horizontally

42200	12 VDC	93	motor driven siren	IP42	<i>(continuous)</i>		84	80
42202	24 VDC	93	motor driven siren	IP42	<i>(continuous)</i>		84	80
42212	240 VAC	93	motor driven siren	IP42	<i>(continuous)</i>		90	129

CELERE series motor driven sirens

- Self-extinguishing PC body with high impact resistance
- Motor protection thermal circuit breaker installed on CELERE and superCELERE versions.
- Easy installation by means of the integrated fixing bracket - M12 cable gland

Mini-CELERE miniature electro-mechanical siren

42006	12 VDC	101	motor driven siren	IP43	<i>(continuous)</i>		91	115
42001	24 VAC/DC	101	motor driven siren	IP43	1 min.	10 min.	91	115
42005	240 VAC/DC	101	motor driven siren	IP43	1 min.	10 min.	91	115

CELERE mid sized electro-mechanical siren

42026	12 VDC	110	motor driven siren	IP43	<i>(continuous)</i>		118	167
42021	24 VAC/DC	110	motor driven siren	IP43	1 min.	10 min.	118	167
42025	240 VAC/DC	110	motor driven siren	IP43	1 min.	10 min.	118	167

Super-CELERE large size electro-mechanical siren

42046	12 VDC	114	motor driven siren	IP43	<i>(continuous)</i>		140	186
42047	24 VDC	114	motor driven siren	IP43	<i>(continuous)</i>		140	186
42045	240 VAC/DC	114	motor driven siren	IP43	1 min.	10 min.	140	186

Electronic sirens

SE4/29 series modular base mount sirens

- Adjustable volume regulation and sound progression regulation
- 5 selectable sound tones
 - Continuous 1000 Hz
 - Bi-tone 600/700 Hz
 - Multi-tone 1000-1700 Hz
 - Modulated 1000-1700 Hz
 - Two-tone 440/560 Hz *for evacuation*

50415	12 - 24 VAC/DC	97	electronic siren	IP30	<i>(continuous)</i>		100	90
50418	240 VAC	97	electronic siren	IP30	<i>(continuous)</i>		100	90

SE12 series electronic sirens (hinged mounting bracket)

- Adjustable volume regulation and sound progression regulation
- 32 different tones (*selectable via dip-switches*) frequency ranges 300/2850 Hz

50424	12 - 24 VAC/DC	114	electronic siren	IP43	<i>(continuous)</i>		102	108
50427	240 VAC	113	electronic siren	IP43	<i>(continuous)</i>		130	108