



GQ22-11



GQ22L-11ER



SB7-CA45R



BPR..K



RZ3A1A60S3



C1700HO



C1760HO

Vandal-proof stainless steel pushbuttons (IP65)

The GQ22 range of vandal-proof pushbuttons, aesthetically pleasing, mount Ø 22 mm illuminated versions feature a LED ring type illumination with clear visibility from a distance.

- Contact rating: lth 5A - Ui 250V
- Termination: Screw terminals
- Illumination: LED (ring indication)

type	colour	contact	mounting hole Ø	description
GQ22-11/S	s/steel	1NO+1NC	Ø 22 mm	vandal-proof flush pushbutton
Illuminated pushbuttons				24 VAC/DC
GQ22L-11ER02S	red	1NO+1NC	Ø 22 mm	LED illuminated pushbutton
GQ22L-11EG02S	green	1NO+1NC	Ø 22 mm	LED illuminated pushbutton
GQ22L-11EY02S	yellow	1NO+1NC	Ø 22 mm	LED illuminated pushbutton
GQ22L-11EB02S	blue	1NO+1NC	Ø 22 mm	LED illuminated pushbutton
GQ22L-11EW02S	white	1NO+1NC	Ø 22 mm	LED illuminated pushbutton

Econo one-piece pushbuttons Ø22mm (IP40)

SB7-CA45R	red	1NO+1NC	Ø 22 mm	one-piece flush pushbutton
SB7-CA35G	green	1NO+1NC	Ø 22 mm	one-piece flush pushbutton
SB7-CA25B	black	1NO+1NC	Ø 22 mm	one-piece flush pushbutton
SB7-CD25B	black	1NO+1NC	Ø 22 mm	two position selector switch

Panel mount potentiometer (IP65)

Mounting: Mounts through standard Ø 22.5 mm pushbutton hole
 Rated power: Linear 1.5W (70°C)
 Isolation resistance: Min 10 MΩ (500V DC)
 Operating temp: -5 - +40°C

BPR01K	1 kΩ	panel mnt	Ø 22 mm	one-piece potentiometer
BPR05K	5 kΩ	panel mnt	Ø 22 mm	one-piece potentiometer
BPR10K	10 kΩ	panel mnt	Ø 22 mm	one-piece potentiometer

Panel mount electronic timer (IP65)

Function: On-Delay timer Range: 0 - 60 seconds
 Mounting: Mounts through standard Ø 2.5 mm pushbutton hole
 Supply voltage: 24 VDC
 Switching current: 200 mA
 Indication: Facia illuminates - green during timing / red - at time lapse
 Operating temp: -5 - +55°C

RZ3A1A60S3	0 - 60 sec	10 - 30 VDC	Ø 22 mm	on-delay panel mnt. analog timer
-------------------	------------	-------------	---------	----------------------------------

Toggle switches 16A 250 VAC single and double pole

type	current lth	switch	mounting hole Ø	description
------	-------------	--------	-----------------	-------------

Series 1700 toggle switches 6.3 mm tab terminals (accepts 6.3 mm push-on lugs)

- Insulated nylon toggle (mounts through Ø 12.7 mm panel hole)
- Approvals: UL 85°C, file E45221 / CSA file LR10990

C1700HO	16A	on-off	Ø 12.7 mm	single pole single throw	SPST
C1710HO	16A	on-on	Ø 12.7 mm	single pole double throw	SPDT
C1720HO	16A	on-off-on	Ø 12.7 mm	s/pole d/throw - centre off	SPDT
C1750HO	16A	on-off	Ø 12.7 mm	double pole single throw	DPST
C1760HO	16A	on-on	Ø 12.7 mm	double pole double throw	DPDT
C1770HO	16A	on-off-on	Ø 12.7 mm	d/pole d/throw - centre off	DPDT

Accessories for toggle switches

F00232PAAA	-	on - off		legend plate for toggle switches
A1080MOAAA	black	cover		toggle rubber boot protection