



MIKE pendant control stations

MIKE pendant stations are designed for heavy duty applications. The mounted rubber pushbuttons guarantees total protection against dust and the moulded two colour button discs offer permanent, clear symbols and text. The new ergonomic shape, design and compact dimensions incorporating antislip grooves on the case reduce fatigue and improving ease of use under any working conditions. Wiring and maintenance are improved by separating the actuators (*mounted on top cover*) from the contact blocks (*fixed to the base together with the cable inlet*) and the innovative hanging system with cables concealed within the housing shell.

- Additional actuator with up to 3 contacts can mounted to the pendant station (*front or bottom base*)
- Weather resistant materials with guaranteed protection against penetration of water and dust
- Operational ambient temperature limits: -40°C - +80°C
- Protection degree: IP66 / IP67 / IP69K Class II insulation
- Mechanical life: 1 x 10⁶ operations
- Conformity to standards: IEC/EN 60204-1, 60947-1, 60947-5-1, 60529, EN418

type	description	reset/ alarm 2NO	Mushroom E/stop 1NC	1 speed button 1NO	2 speed button 1NO+1NO
------	-------------	------------------------	---------------------------	--------------------------	------------------------------

MIKE series *single row pendant control station (IP66)*

F70AY120200-2	4 way	pendant station	1	1	2	-
F70AY120002-2	4 way	pendant station	1	1	-	2
F70AY000400-1	4 way	pendant station	-	-	4	-
F70AY000202-5	4 way	pendant station	-	-	2	2
F70AY000004-1	4 way	pendant station	-	-	-	4
F70EY120400-1	6 way	pendant station	1	1	4	-
F70EY120004-1	6 way	pendant station	1	1	-	4
F70EY120202-1	6 way	pendant station	1	1	2	2
F70BY120600-2	8 way	pendant station	1	1	6	-
F70BY120006-2	8 way	pendant station	1	1	-	6
F70CY121000-2	12 way	pendant station	1	1	10	-
F70DY121200-2	14 way	pendant station	1	1	12	-

Extra charges on request, standard elements can be replaced by others (see below)

- 1/2 SPD double depression 2 speed button and contact instead of 1 speed
- 1/2 MSRM double depression 2 speed button and contact instead of mushroom + reset
- 1/1 MSRM single depression 1 speed button and contact instead of mushroom + reset

Accessories for MIKE pendants stations (above) *(W) 84.5 x (D) 59.5 x (H) ↓ mm*

F70AY000000-1	4 way	black/yellow	empty pendant housing only	427
F70EY000000-1	6 way	black/yellow	empty pendant housing only	487
F70BY000000-1	8 way	black/yellow	empty pendant housing only	547
F70CY000000-1	12 way	black/yellow	empty pendant housing only	667
F70DY000000-1	14 way	black/yellow	empty pendant housing only	727

also available in all black colour

Victor wall mounted control stations (empty housings)

Victor has been designed to facilitate wiring and maintenance. Contact blocks are installed in the base together with the cable inlet and are separated from the actuators installed on the cover, reducing time, cost of installation and maintenance down time.

- Protection degree: IP66/IP67/IP69K Insulation category: Class II
- Operational ambient temp: -40°C - +80°C Cable entry: cable clamp M20 x 1.5

type	colour top cover	actuators	description	(W) 72.7 x (D) 61.9 x (H) ↓ mm
------	---------------------	-----------	-------------	--------------------------------

F71EY000000-1	yellow	1 hole	empty surface mnt control station	73
F71EG000000-1	grey	1 hole	empty surface mnt control station	73
F71FG000000-1	grey	2 hole	empty surface mnt control station	122
F71GG000000-1	grey	3 hole	empty surface mnt control station	152
F71HG000000-1	grey	4 hole	empty surface mnt control station	182
F71IG000000-1	grey	6 hole	empty surface mnt control station	242
F71JG000000-1	grey	8 hole	empty surface mnt control station	302

Contact blocks for pendant and control stations (screw termination)

- Rated operational current 3A (AC15) / voltage 250V • Thermal current: 10A
- NC contact blocks are of positive operating type

PRSL1800PI	1 NO	contact block	for above control stations
PRSL1801PI	1 NC	contact block	for above control stations
PRSL1820PI	LED	24/48 VAC/DC	LED indicating lamp element
PRSL1821PI	LED	110/230 VAC	LED indicating lamp element