




91131



91132



91153



911...



91177



91184

Panel mount Ø30 mm signalling devices

P40 small panel mounting signalling devices developed with multifunctional technology, permitting different levels of alarm selectable via independent electric contacts. Self-extinguishing PC body totally protected against vibration, dust and atmospheric elements.

- Up to IP66 protection (*acoustic devices IP65*)
- Multi-voltage: 12/24 VAC/DC (or) 48 - 240 VAC
- 4 bright LEDs, lense with 360° light diffusion with maximized frontal performance
- Mounts through Ø 30 mm hole secured with locking ring provided (*internal depth max. 37 mm*)

type	lens colour	dB @ 1 m max	supply	description	dimensions (mm)	
					Ø	ext.

P40 S - multi-functional LED signalling panel beacon (IP66)

- 3 levels of alarm : steady - flashing - strobe (*selectable via electrical contacts*)

91131	blue	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91132	amber	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91133	red	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91134	green	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91135	yellow	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91136	clear	–	12 - 24 VAC/DC	panel mnt signaling device	41	46
91151	blue	–	48 - 240 VAC	panel mnt signaling device	41	46
91152	amber	–	48 - 240 VAC	panel mnt signaling device	41	46
91153	red	–	48 - 240 VAC	panel mnt signaling device	41	46
91154	green	–	48 - 240 VAC	panel mnt signaling device	41	46
91155	yellow	–	48 - 240 VAC	panel mnt signaling device	41	46
91156	clear	–	48 - 240 VAC	panel mnt signaling device	41	46

P40 RGA - multicolour (red-green-amber) LED panel beacon (IP66)

- 3 levels of alarm: red - green - amber light (*selectable via electrical contacts*)

91167	white	flashing	12 - 24 VAC/DC	multicoloured LED beacon	41	46
91168	white	steady	12 - 24 VAC/DC	multicoloured LED beacon	41	46
91171	white	flashing	48 - 240 VAC	multicoloured LED beacon	41	46
91172	white	steady	48 - 240 VAC	multicoloured LED beacon	41	46

P40 A - piezoelectric panel mount acoustic sounder (IP65)

- 2 levels of alarm: continuous - intermittent sound (*selectable via electrical contacts*)

91177	grey	85dB	12 - 24 VAC/DC	panel mnt audible sounder	41	34
91179	grey	85dB	48 - 240 VAC	panel mnt audible sounder	41	34

P40 A LED - combination sounder and signal beacon (IP65)

- 3 levels of alarm:

LEVEL 1	alert	flashing light only
LEVEL 2	pre-alarm	flashing light + intermittent sound
LEVEL 3	alarm	steady light + continuous sound

91182	amber	85dB	12 - 24 VAC/DC	panel mnt signaling device	41	34
91183	red	85dB	12 - 24 VAC/DC	panel mnt signaling device	41	34
91184	green	85dB	12 - 24 VAC/DC	panel mnt signaling device	41	34
91202	amber	85dB	48 - 240 VAC	panel mnt signaling device	41	34
91203	red	85dB	48 - 240 VAC	panel mnt signaling device	41	34
91204	green	85dB	48 - 240 VAC	panel mnt signaling device	41	34