



- Cooling capacity to: DIN 3168
- Connection: Terminal block
- Operating temp. range: 20°C - 55°C
- Housing: Mild steel, powder coated (*available in stainless steel*)
- Colour: RAL 7035 (*other colours available on request*)
- Supply: 230V - 50/60Hz (*others on request*)

ComPact series economical all-round systems

ComPact series air conditioners optimise high efficiencies with outstanding COP values throughout the range, the built-in controller displays temperature, operating status and can be simply adjusted. Surface treated condenser with high fin separation provide virtually maintenance free service.

- Compressor type: Reciprocating compressor
- Mounting: External

type	cooling capacity L35L35	supply voltage	description	dimensions (mm)		
				(W)	(D)	(H)
43040001	320W	230 VAC	ComPact air conditioner	500	280	200
43050001	550W	230 VAC	ComPact air conditioner	650	315	260
43080001	750W	230 VAC	ComPact air conditioner	650	315	260
43100001	1000W	230 VAC	ComPact air conditioner	650	315	260
43150001	1500W	230 VAC	ComPact air conditioner	980	395	260
43200001	2000W	230 VAC	ComPact air conditioner	980	395	260

Larger sizes up to 4.0 kW available on request

Accessories for above compact air conditioners

- 82000001** condensate evaporator (*evaporation box*) for above (0.25L / h)

SlimLine series filter less technology air conditioners

SlimLine series air conditioners provide maximum power-to-size ratio compatible with market standards ensuring simple integration with cabinet systems. Designed to operate with minimum maintenance, due to eco-friendly filter less construction. The optimised wide-ribbed aluminium condenser provides improved cooling performance ensuring total reliability in all industrial applications.

Can be mounted externally or internally (*with only 25 mm protruding when recess mounted*)

- Compressor type: Rotary piston compressor
- Mounting: Internal / External
- Supply: 230V - 50/60Hz (*others on request*)

42660001	320 W	230 VAC	SlimLine air conditioner	520	270	110
42690001	500 W	230 VAC	SlimLine air conditioner	600	320	110
42700001	600 W	230 VAC	SlimLine air conditioner	810	395	145
42710001	820 W	230 VAC	SlimLine air conditioner	980	395	145
42720001	1100 W	230 VAC	SlimLine air conditioner	1250	395	145
42740001	1500 W	230 VAC	SlimLine air conditioner	1550	395	145

Top mounted filter less slimline air conditioners

- Compressor type: Rotary piston compressor
- Mounting: Roof mounting
- Supply: 230V - 50/60Hz

44820001	450 W	230 VAC	roof mount air conditioner	230	430	330
45550001	1100 W	230 VAC	roof mount air conditioner	400	600	400

Larger sizes available on request

Variable speed DC air conditioner

- Compressor type: Speed controlled rotary compressor
- Mounting: Internal / External

20250240	120 - 450W	24 VDC	SlimLine air conditioner	465	296	85
20250480	120 - 450W	48 VDC	SlimLine air conditioner	465	296	85