



TG series thermoelectric cooling units (heat pumps) IP55

For cooling enclosures or electronic components

Thermoelectric cooling units an effective solution for the conditioning of enclosures or electronic components. Electric energy transferred heat without the use of hazardous gases or liquids. The core of the system are thermoelectric modules (*Peltier modules*) permitting heat absorption from one side (*cold side*) and heat expulsion to the ambient from the other side.

- Eco-friendly
- Maintenance free
- Operation in any orientation
- Easy installation

type	voltage (V)	cooling power	rated current	cutout (mm)	dimensions (mm)		
					H	W	D
TG 3102-24V	24 VDC	100W	4.8A	260 x 160	200	304	138
TG 3200-24V	24 VDC	200W	9.0A	370 x 155	400	180	171

Drip trays (to collect condensate from the cold internal dissipator)

- TCU 100** stainless steel drip tray for above TG 3102-24V thermoelectric units
- TCU 200** stainless steel drip tray for above TG 3200-24V thermoelectric units

Seifert SL 4000 series panel lamps (IP20)

Seifert new stripLite LED light fixture is the economical and space saving solution for cabinet and enclosure lighting. The state of the art LED technology ensures a long and maintenance free life cycle.

- Motion sensor or ON/OFF switch available
 - Various fitting options for more flexibility
 - Wieland connector for fast and easy installation
 - Combined AC and DC voltage range allows the universal with a single model
 - Daisy chain cables allow to connect up to 16 lights and with AC and up to 8 lights with DC voltage
- Operating voltage: 24 - 265 VAC/DC
 - Operating temp: -30 to 70°C
 - Approvals: CE, cURus
 - LED: 400 Lm, 120°, daylight, colour temperature 6500K

type	power	description	dimensions (mm)		
			H	W	D
400100	4 Watt	LED panel lamp with on/off rocker switch	32	350	28
400000	4 Watt	LED panel lamp with infrared sensor	32	350	33

Plug-in connectors for above SL4000 panel lamps

91.921.3053.0	white	female connector plug for panel lamps	18	53	14
91.922.3053.0	white	male connector plug for panel lamps	18	53	14

Note: Termination via 2 pin latching plug (supplied separately) on both ends of the lamp with release button. Fastening via supplied mounting clips or incorporated magnets for simple positioning on metallic surfaces.