



Busbar supports for Quadro system

All accessories are designed for adapting enclosures to accommodate a range of components

- Perforations in profiles, brackets, rails are in steps 25 mm apart and accommodate cage nuts M6 (UC900)

type	current	bar size		pole	description	dimensions	
		width (mm)	thick (mm)			length (mm)	width (mm)
Side busbar support							
UC830	250A	20	5	4	side mounting busbar supports kit (2)	-	-
UC834	-	-	-	-	protective screen for above supports	1000	-
Multi stage busbars support							
UC815	400A	32	5	4	stepped busbar support (1)	-	-
UC288					universal crossbars for mounting UC815	-	185
UC289					universal crossbars for mounting UC816	-	500
UC988					universal crossbars for mounting UC815	-	250
UC816					protective screen for above supports	620	170
Flat busbar support							
UC820	630A	20/30	5/10	4	busbar support for flat bars (1)	-	-
UC812					support kit for rear vertical mounting	-	250
UC289					universal crossbars for mounting	-	500
UC827					protective screen for above support	620	-
Inclined busbar supports							
UC826	630A	30	10	4	inclined staged bars (2)	-	-
UC828	250A				protective screen for above support	990	212
Universal busbar support (adjustable)							
UC895E	3200A	30 - 120	5	4	support kit for 5 mm bars (up to 4 bars per phase)		
UC896E	3200A	30 - 120	10	4	support kit for 10 mm bars (up to 2 x busbars per phase)		
UC897E	3200A	30 - 120	10	4	support kit for 10 mm bars (up to 3 x busbars per phase)		
UC860E					perforated aluminium profile for support kit	2 met.	-
UC861E					bracket kits for above UC860E	-	-