








	type	range	description		price
	BEA40A				
	BEV40A				
	BEF50AP				
	BEF50AR				
	BEMC01A				
	BEHCA4				
	BEHCD4				
Ammeters (AC) moving iron (overscale 2 x In) (90° movement)					
	BEA01A*	1A	direct reading AC ammeter		
	BEA05A*	5A	direct reading AC ammeter		
	BEA10A*	10A	direct reading AC ammeter		
	BEA15A*	15A	direct reading AC ammeter		
	BEA25A*	25A	direct reading AC ammeter		
	BEA40A*	40A	direct reading AC ammeter		
	BEA01AT*	1A	CT operated AC ammeter		
	BEA05AT*	5A	CT operated AC ammeter		
Voltmeters (AC) moving iron (90° movement)					
	BEV25A	250V	direct reading AC voltmeter		
	BEV40A	400V	direct reading AC voltmeter		
	BEV50A	500V	direct reading AC voltmeter		
	BEV60A	600V	direct reading AC voltmeter		
Frequency meters (90° movement)					
	BEF50AP*	45 - 55Hz	frequency (pointer type) 110 - 380V		
	BEF50AR*	47 - 53Hz	frequency (vibrating reed) 110 - 230V		
	BEF50AR*3	47 - 53Hz	frequency (vibrating reed) 380 - 500V		
Maximum demand ammeters (90° movement) delay time: 15 min (standard)					
	ERB01A*	/1A	maximum demand ammeters		
	ERB05A*	/5A	maximum demand ammeters		
Combination maximum demand ammeters					
	ERBC01A*	/1A	com. Max. demand ammeters		
	ERBC05A*	/5A	com. Max. demand ammeters		
Power factor indicator (90° movement) 230 - 380V					
	BEP05A*	/5A	power factor indicator (0.5 - 1 - 0.5)		
Ammeters (DC) moving coil (90° movement)					
	BEA05D*	5A	direct reading DC ammeter		
	BEA10D*	10A	direct reading DC ammeter		
	BEA15D*	15A	direct reading DC ammeter		
	BEA20D*	20A	direct reading DC ammeter		
	BEA25D*	25A	direct reading DC ammeter		
	BEA30D*	30A	direct reading DC ammeter		
	BEV50MVD**	50mV	shunt operated ammeter		
	BEA01MAD*	1mA	DC (low current) ammeter		
	BEA20MAD*	4 - 20mA	DC (low current) ammeter		
	** For DC shunts please refer to page E-20				
Voltmeter (DC) (90° movement)					
	BEV03D*	0 - 30V	DC voltmeter		
	BEV15D*	1 - 150V	DC voltmeter		
	BEV60D*	150 - 600V	DC voltmeter		
Extra charges and accessories					
144 mm ² housing (90° movement) – add to 96 mm ² price					
coloured bezels R / W / B for instruments					
IP65 housing front protection					
spare glass					
Running hour meters					
	BEHCA*	AC	running hour meter 24/110/230/380 VAC		
	BEHCD*	DC	running hour meter 10 - 80 VDC		
	* 4 = 48 x 48 mm / 7 = 72 x 72 mm / 9 = 96 x 96 mm				