




JDY25/P



JDY25/PI040



BFA...

- Complete with:
- Start, stop/reset pushbuttons (*pilot light can be incorporated*)
 - Thermal overload relay (*phase failure sensitive*)
 - Integral control terminals for ease of wiring

type	motor rating	overload range (x 0.58 of full load)	description	dimensions (mm)		
				(H)	(W)	(D)

Enclosed star-delta starters (IP65)

ABS enclosure M3N (hinged door 180° opening)

JDY9/P	7.5kW	6.3 - 10A	enclosed star-delta starter	233	280	191
JDY12/P	11.0kW	9 - 14A	enclosed star-delta starter	233	280	191
JDY18/P	15.0kW	13 - 18A	enclosed star-delta starter	233	280	191
JDY25/P	18.5kW	17 - 23A	enclosed star-delta starter	233	280	191
JDY26/P	22.0kW	24 - 32A	enclosed star-delta starter	233	280	191
JDY38/P	30.0kW	32 - 38A	enclosed star-delta starter	233	280	191

Sheet metal enclosure (IP65)

JDY9/M2	7.5kW	6.3 - 10A	enclosed star-delta starter	450	300	220
JDY12/M2	11.0kW	9 - 14A	enclosed star-delta starter	450	300	220
JDY18/M2	15.0kW	13 - 18A	enclosed star-delta starter	450	300	220
JDY25/M2	18.5kW	17 - 23A	enclosed star-delta starter	450	300	220
JDY26/M2	22.0kW	24 - 32A	enclosed star-delta starter	450	300	220
JDY38/M2	30.0kW	32 - 38A	enclosed star-delta starter	450	300	220
JDY50/M4	37/45kW	35 - 50A	enclosed star-delta starter	650	450	270
JDY65/M4	55kW	46 - 65A	enclosed star-delta starter	650	450	270
JDY80/M4	75kW	60 - 82A	enclosed star-delta starter	650	450	270
JDY115/M5	110kW	75 - 125A	enclosed star-delta starter	750	550	270
JDY145/M5	132kW	90 - 150A	enclosed star-delta starter	750	550	270
JDY180/M5	160kW	120 - 200A	enclosed star-delta starter	750	550	270
JDY250/M7E	250kW	150 - 250A	enclosed star-delta starter	950	700	330
JDY400/M7E	375kW	250 - 420A	enclosed star-delta starter	950	700	330

Larger sizes available on request

With mounted on-load isolator (extra charge)

- Padlockable in OFF position, door interlocking in ON position

I040*	isolator	with padlockable door interlocking isolator	up to 18.5kW
I063*	isolator	with padlockable door interlocking isolator	up to 30.0kW
I125*	isolator	with padlockable door interlocking isolator	up to 55.0kW
I160*	isolator	with padlockable door interlocking isolator	up to 75.0kW
I315*	isolator	with padlockable door interlocking isolator	up to 160.0kW
I630*	isolator	with padlockable door interlocking isolator	up to 375.0kW

* Add end of starter part number

Extra charges

pilot light "trip" or "run" indication incorporated into pushbuttons
with door mounted ammeter or voltmeter

Open type pre-assembled star-delta starters (complete with thermal overload relay)

- Fully assembled and wired with mounted star-delta timer and thermal overload relay
- Integral control terminals for ease of wiring

BFA009.10	7.5kW	6.3 - 10A	open frame complete star-delta starter
BFA012.14	11.0kW	9 - 14A	open frame complete star-delta starter
BFA018.18	15.0kW	13 - 18A	open frame complete star-delta starter
BFA025.23	18.5kW	17 - 23A	open frame complete star-delta starter
BFA026.32	22.0kW	24 - 32A	open frame complete star-delta starter
BFA038.38	30.0kW	32 - 38A	open frame complete star-delta starter
BFA050.42	37.5/45kW	35 - 42A	open frame complete star-delta starter
BFA065.65	55kW	46 - 65A	open frame complete star-delta starter
BFA080.82	75kW	60 - 82A	open frame complete star-delta starter
NYF115.125	110kW	75 - 125A	open frame complete star-delta starter
NYF145.150	132kW	90 - 150A	open frame complete star-delta starter
NYF180.200	160kW	120 - 200A	open frame complete star-delta starter
NYF250.250	250kW	150 - 250A	open frame complete star-delta starter
NYF400.420	375kW	250 - 420A	open frame complete star-delta starter