

GST multipole connectors						
 91.931.3053.0  91.932.3053.0  91.931.9053.0  91.932.9053.0  91.030.4953.0  92.931.3053.1  92.932.3053.1  92.030.4853.1  92.031.9658.1  73.300.0353.0  73.310.0353.0  76.320.0729.0  76.352.0736.1		<p>Rated voltage: 250V Rated current: 16A Protection degree: IP 20 Colour: white (<i>black available on request</i>)</p> <ul style="list-style-type: none"> Quick, easy and reliable connection technology 				
type	amps	poles	for cable Ø mm	wire mm ²	description	
GST 15i3 (Gesis mini) connectors 16A/250V 3 pole						
<ul style="list-style-type: none"> Integrated locking device 						
In-line connectors (with strain relief)			<i>screw connection</i>			
91.931.3053.0	16A	3 pole	5.5 - 8.5	0.5 - 1.5	female in-line connector	
91.932.3053.0	16A	3 pole	5.5 - 8.5	0.5 - 1.5	male in-line connector	
Panel mounting			<i>screw connection</i>			
91.931.9053.0	16A	3 pole	–	0.5 - 1.5	flush female p/mnt connector	
91.931.9153.0	16A	3 pole	–	0.5 - 1.6	protruding female p/mnt conn.	
91.932.9053.0	16A	3 pole	–	0.5 - 1.5	flush male p/mnt connector	
91.932.9153.0	16A	3 pole	–	0.5 - 1.6	protruding male p/mnt conn.	
Accessories for GST15i connectors						
91.030.6053.0	16A	3 pole	1 in / 2 out distribution unit for GST15i connectors			
91.030.4953.0	16A	3 pole	1 in / 3 out distribution unit for GST15i connectors			
91.030.5853.0	16A	3 pole	U-type intermediate coupling for GST 15i connectors			
91.030.5953.0	16A	3 pole	in-line intermediate coupling for GST 15i connectors			
GST 18i3 (Gesis) connectors 16A/250V 3 pole						
In-line connectors (with strain relief)			<i>screw connection</i>			
92.931.3053.0	16A	3 pole	6.5 - 10.5	0.75 - 2.5	female in-line connector	
92.932.3053.0	16A	3 pole	6.5 - 10.5	0.75 - 2.5	male in-line connector	
Panel mounting (snap-in)			<i>spring-loaded screwless connection</i>			
92.031.9658.0	16A	3 pole	–	0.75 - 2.5	female panel mount connector	
92.032.9658.0	16A	3 pole	–	0.75 - 2.5	male panel mount connector	
Accessories for GST18i connectors						
92.030.4853.0	16A	3 pole	1 in / 2 out distribution unit for GST18i connectors			
92.030.5958.0	16A	3 pole	in-line intermediate coupling for GST 18i connectors			
05.587.3156.0						locking device for in-line connectors
05.561.3653.0						protection cover for GST18i female connectors
Revos MINI 10A/400V 3/4 pole + earth						
Rated voltage: 690V Rated current: 10A Protection degree: IP 65 connection: screw terminal		<ul style="list-style-type: none"> Made up with contact insert (<i>male and female</i>) - base - hood 				
type	poles	amps	connect	description		
Contact inserts screw connection						
73.310.0353.0	3 pole	10A	screw	male plug contact insert		
73.310.0453.0	4 pole	10A	screw	male plug contact insert		
73.300.0353.0	3 pole	10A	screw	female socket contact insert		
73.300.0453.0	4 pole	10A	screw	female socket contact insert		
Bases with locking lever						
76.320.0729.0	3/4	–	open	straight	metal base	
76.321.0729.0	3/4	–	open	90°	metal angled base	
76.320.0753.0	3/4	–	open	straight	plastic base base	
76.321.0753.0	3/4	–	open	90°	plastic angled base	
Hoods with threaded collar						
76.352.0736.1	3/4	–	M20	straight	metal hood	
76.350.0736.1	3/4	–	M20	90°	metal angled hood	
76.352.0760.1	3/4	–	M20	straight	plastic hood	
76.350.0760.1	3/4	–	M20	90°	plastic angled hood	