



Unibox series surface mounting weatherproof switches and sockets (IP55)

- Housing: Engineering plastic (*halogen free*) RAL 7035 (*grey*)
- Impact resistance: IK06 (*500g with a striking energy of 1J*)
- Max. temperature: +60°C
- Glow wire test: 650°C

type	amps	poles	description	dimensions (mm)		
				(H)	(W)	(D)

Unibox series surface mounting (IP55)

1 gang surface mount switches (IP55)

136.5121-303	16A	1P	1-way surface mount switch	82	68	66
136.5121-302	20A	2P	1-way surface mount switch	82	68	66
136.5121-323	16A	1P	2-way surface mount switch	82	68	66
136.5121-333	16A	1P	bell-push (momentary action)	82	68	66

2 gang surface mount switches (IP55)

136.5122-303	16A	2P	2 x 1-pole surface mount switch	82	68	66
---------------------	-----	----	---------------------------------	----	----	----

3 gang surface mount switches (IP55)

136.5123-303	16A	3P	3 x 1-pole surface mount switch	82	98	66
---------------------	-----	----	---------------------------------	----	----	----

Surface mount switch socket (IP55)

136.5123-414	15A	2P+E	2-pole + earth switch socket outlet	82	98	66
---------------------	-----	------	-------------------------------------	----	----	----

Accessories for Unibox series

136.5121	1 gang surface mount empty housing only	(IP55)	82	68	66
136.5122	2 gang surface mount empty housing only	(IP55)	82	68	66
136.5123	3 gang surface mount empty housing only	(IP55)	82	98	66
136.001	external mount brackets for surface boxes	(2 pcs)			

570.5052*	2 gang panel mount housing for switches or socket	82	68	–
570.6001*	2 gang panel mount housing (IP66 with plug inserted)	107	84	–
136.5023	3 gang flush mount housing only for switches or sockets	82	98	–
875.4303	3 gang wall box for flush mount empty housing	82	98	–

* Fits into housing for industrial sockets with 70 x 87 mm flange

Evolution series switches and sockets for above boxes

101.6303.G	16 A 1-pole switch for housings	(1 module)
101.6414.G	15A 2-pole and earth socket for housings	(2 module)

Protecta series switches and sockets (IP66)

- Housing: Engineering plastic (*halogen free*) RAL 7035 (*grey*)
- Mounting: Surface mount (*can be flush mounted*)
- Max. temperature: +60°C
- Glow wire test: 850°C

1 gang surface mount switches (IP66)

137.5012	20A	1P	surface mount switch	IP66	95	95	–
137.5462	20A	2P	surface mount switch	IP66	95	95	–
137.5212	20A	1P	2 way surface mount switch	IP66	95	95	–
137.5311P	10A	1P	bell-push (<i>momentary action</i>)	IP66	95	95	–

2 gang surface mount switches (IP66)

137.5022	20A	2P	surface mount switch	IP66	95	95	–
-----------------	-----	----	----------------------	------	----	----	---

Switch socket outlet IP66 (unique sealing of cable inlet)

137.6111	15A	2P+E	2 pole + earth switch socket outlet	115	115	–
-----------------	-----	------	-------------------------------------	-----	-----	---

Accessories for above Protecta switches

137.101	surface mount back box for above switches	95	95	–	
137.141	pole mount back box for above switches	95	95	–	
137.002	IP66 cover accepts 2 x evolution (<i>modules</i>)			–	
137.121	flush mount frame kit for above switches	95 x 95 mm	95	95	–
137.123	flush mount frame kit for above sockets	115 x 115 mm	115	115	–