RST connectors are an ideal solution to providing pluggable connections to products able to withstand severe conditions, the connectors easily replace conventional cable glands providing a flexible, pluggable solution.

- Rapid mounting through ease of handling
 UV-resistant (Polymide Halogen free)
- Cross-sections up to 6 mm²

• Protection degree: IP65, IP66, IP67, IP68, IP69K

· Colour: Black

type	current (A)	No. poles	for cable (Ø mm)	wire (mm²)	description	panel hole Ø		
RST MINI Twistlock technology 250V								
RST 16i3	16A	3 pole						
46.031.4553.1	16A	3 pole	5 - 9.5	.25 - 1.5	in-line female connector	_		
46.032.4553.1	16A	3 pole	5 - 9.5	.25 - 1.5	in-line male connector	_		
46.031.5053.1	16A	3 pole	-	.25 - 1.5	panel mnt female connector	M16		
46.032.5053.1	16A	3 pole	_	.25 - 1.5	panel mount male connector	M16		
.0.002.0000.		o po.o		00	paner meant male connecter			
46.030.1253.1	16A	3 pole	-	-	1in / 2out distribution block	-		
Z6.561.7253.1	16A	3 pole	•		bove 3 pole female connectors	-		
Z6.561.6953.1	16A	3 pole	prote	ction cover to	or above 3 pole male connectors	-		
RST 16i5	16A	5 pole						
46.051.4553.1	16A	5 pole	5 - 9.5	.25 - 1.5	in-line female connector	-		
46.052.4553.1	16A	5 pole	5 - 9.5	.25 - 1.5	in-line male connector	-		
46.051.5053.1	16A	5 pole	-	.25 - 2.5	panel mnt female connector	M20		
46.052.5053.1	16A	5 pole	-	.25 - 2.5	panel mount male connector	M20		
46.050.1253.1	16A	5 pole	-	-	1in / 2out distribution block	-		
06.562.5853.1	16A	3/5 pole	mounting base for above 3/5 pole distribution blocks			-		
Z6.561.7153.1	.561.7153.1 16A 5 pole protection cover for above 5 pole female connectors –							
Z6.561.6853.1	16A	5 pole			above 5 pole male connectors	_		
			0.5	2) (
RST 20i3	20A	3 pole	250	JV				
96.031.4053.1	20A	3 pole	6 - 10	.75 - 6.0	in-line female connector	-		
96.031.4153.1	20A	3 pole	10 - 14	.75 - 6.0	in-line female connector	_		
96.032.4053.1	20A	3 pole	6 - 10	.75 - 6.0	in-line male connector	_		
96.032.4153.1	20A	3 pole	10 - 14	.75 - 6.0	in-line male connector	_		
96.031.5053.1	20A	3 pole	_	.75 - 6.0	panel mnt female connector	M25		
96.032.5053.1	20A	3 pole	_	.75 - 6.0	panel mount male connector	M25		
RST 20i5	20A	5 pole			F			
		•	10 11	75 40	in line female connector			
96.051.4153.1	20A	5 pole	10 - 14	.75 - 4.0	in-line female connector	_		
96.052.4153.1	20A	5 pole	10 - 14	.75 - 4.0	in-line male connector	_		
96.051.4353.1	20A	5 pole	10 - 14	.75 - 1.5	female splitter connector			
96.051.5053.1	20A	5 pole	-	.75 - 4.0	panel mnt female connector	M25		
96.052.5053.1	20A	5 pole	-	.75 - 4.0	panel mount male connector	M25		
96.031.4253.1	20A	3/5 pole	6 - 10	.75 - 2.5	female splitter connector	_		
96.031.4353.1	20A	3/5 pole	10 - 14	.75 - 2.5	female splitter connector	_		
01.006.1553.1	20A	3/5 pole				_		
		•	mounting plate for 20A 3/5 pole splitter connector					
RST 25i3	32A	(using (6 mm² cab	ole)	PV applications			
96.031.4554.3	32A	3 pole	10 - 14	.75 - 6.0	in-line female connector	_		
96.032.4554.3	32A	3 pole	10 - 14	.75 - 6.0	in-line male connector	_		
96.031.5054.3	32A	3 pole	_	.75 - 6.0	panel mnt female connector	M25		
96.032.5054.3	32A	3 pole	_	.75 - 6.0	panel mount male connector	M25		
RST 50i5	50A	5 pole			power series			
131 3013	JUA	o pole			power series			
97.051.4053.1	50A	5 pole	15 - 25	4.0 - 16.0	in-line female connector	M32		
97.052.4053.1	50A	5 pole	15 - 25	4.0 - 16.0	in-line male connector	M32		
97.051.5553.1	50A	5 pole	_	4.0 - 16.0	panel mnt female connector	M32		
97.052.5553.1	50A	5 pole	-	4.0 - 16.0	panel mount male connector	M32		
Accessories for RST20/25/50 connectors								
05.564.8653.1	20/32A	_			nnect tool (easy release button)	-		
05.568.8853.1	20/32A	_	spacer ring (manually actuated) for M25 connectors M25					
99.416.6205.2		3 pole	protection cover for 20/32A 3 pole female connector –					
99.414.6205.2	20/32A	3 pole	protection cover for 20/32A 3 pole male connector –					
99.532.0000.7	20/32A	5 pole	protection cover for 20/32A 5 pole female connector –					
99.530.0000.7	20/32A	5 pole	protect	ion cover for	r 20/32A 5 pole male connector	-		

protection cover for 50A male or female connectors

















Z5.567.5653.0 50A