



- Modular DIN rail mounting (*same cutout as MCBs*)
- Feature economic low consumption, low heat dissipation coils

type	contact rating	coil voltage	description	contact config.	width in 17.5 mm
------	----------------	--------------	-------------	-----------------	------------------

Modular contactors

Standard contactors (230 VAC 50/60 Hz)

ESC225	25A	230 VAC	modular standard contactor	2NO	1
ESC226	25A	230 VAC	modular standard contactor	2NC	1
ESC227	25A	230 VAC	modular standard contactor	1NO + 1NC	1
ESC425	25A	230 VAC	modular standard contactor	4NO	2
ESC427	25A	230 VAC	modular standard contactor	2NO + 2NC	2
ESC240	40A	230 VAC	modular standard contactor	2NO	3
ESC241	40A	230 VAC	modular standard contactor	2NC	3
ESC440	40A	230 VAC	modular standard contactor	4NO	3
ESC442	40A	230 VAC	modular standard contactor	2NO + 2NC	3
ESC263	63A	230 VAC	modular standard contactor	2NO	3
ESC463	63A	230 VAC	modular standard contactor	4NO	3
ESC464	63A	230 VAC	modular standard contactor	4NC	3
ESC465	63A	230 VAC	modular standard contactor	2NO + 2NC	3

Relays and contactors with manual override facility

ERC216	16A	230 VAC	modular rail mount relay	2NO	1
ERC218	16A	230 VAC	modular rail mount relay	1NO + 1NC	1
ERC416	16A	230 VAC	modular rail mount relay	4NO	2
ERC418	16A	230 VAC	modular rail mount relay	2NO + 2NC	2
ERC225	25A	230 VAC	modular standard contactor	2NO	1
ERC240	40A	230 VAC	modular standard contactor	2NO	3
ERC263	63A	230 VAC	modular standard contactor	2NO	3

Modular "low noise" contactors

- No humming while energised / low switching noise

ERC225S*	25A	230 VAC	low noise modular contactor	2NO	1
ERC425S*	25A	230 VAC	low noise modular contactor	4NO	2
ESC440S	40A	230 VAC	low noise modular contactor	4NO	3
ESC463S	63A	230 VAC	low noise modular contactor	4NO	3
ERL625SDC*	25A	12 VDC	low noise modular contactor	2NO	1
ERL425SDC*	25A	12 VDC	low noise modular contactor	4NO	2
ESL440S	40A	12 VDC	low noise modular contactor	4NO	3
ESL463S	63A	12 VDC	low noise modular contactor	4NO	3
ERD225SDC*	25A	24 VDC	low noise modular contactor	2NO	1
ESD425SDC*	25A	24 VDC	low noise modular contactor	4NO	2
ESD440S	40A	24 VDC	low noise modular contactor	4NO	3
ESD463S	63A	24 VDC	low noise modular contactor	4NO	3

* With manual override control

Contactors accessories

Auxiliary contact for all above contactors

Auxiliaries are not compatible with low noise contactors **ERC225S, ERL625SDC, ERD225SDC**

ESC080	1th 6A	–	clip-on auxiliary contact	1NO + 1NC	0.5
LZ060*	heat dissipation insert for mounting between contactors				0.5

* Avoid overheating when installed side by side, insert a heat dissipation module **LZ060** between contactors

Modular latching / step relays

- Pulsing the relay changes the contact status until pulsed again
- Max. pulse duration: 1 hour
- With manual override facility

EPN515	16A	230 VAC	modular stepping relay	1NO + 1NC	1
EPN503	16A	48 VAC/24 VDC	modular stepping relay	1NO + 1NC	1
EPN518	16A	24 VAC/12 VDC	modular stepping relay	1NO + 1NC	1
EPN519	16A	12 VAC	modular stepping relay	1NO + 1NC	1
EPN521	16A	12 VAC	modular stepping relay	2NO	1

Auxiliary for above stepping relays

EPN051	1th 6A	–	clip-on auxiliary contact	1NO + 1NC	0.5
EPN053	1th 6A	–	converts maintained contact into a pulsed one	1 C/over	0.5