



ERC216



ERC418



ESC225



ESC425



ERC425S



ESC463S



ESC080



EPN051



EPN053

- Modular DIN rail mounting (*same cut-out as MCBs*)
- One and two module contactors feature economy low consumption, low heat dissipation coils
- Four ratings: 16A, 25A, 40A, 63A

type	rated power		coil voltage	description	contact config.	width in 17.5mm
	AC-1 (A)	AC-3 kW (400V)				
Modular contactors (230 VAC 50/60 Hz)						
ERC216*	16A	–	230 VAC	modular standard contactor	2NO	1
ERC218*	16A	–	230 VAC	modular standard contactor	1NO+1NC	1
ERC416*	16A	1.7kW	230 VAC	modular standard contactor	4NO	2
ERC418*	16A	1.7kW	230 VAC	modular standard contactor	2NO+2NC	2
ESC225	25A	–	230 VAC	modular standard contactor	2NO	1
ERC225*	25A	–	230 VAC	modular standard contactor	2NO	1
ESC226	25A	–	230 VAC	modular standard contactor	2NC	1
ESC227	25A	–	230 VAC	modular standard contactor	1NO+1NC	1
ESC425	25A	2.6kW	230 VAC	modular standard contactor	4NO	2
ESC427	25A	2.6kW	230 VAC	modular standard contactor	2NO+2NC	2
ESC240	40A	7.8kW	230 VAC	modular standard contactor	2NO	3
ERC240*	40A	7.8kW	230 VAC	modular standard contactor	2NO	3
ESC241	40A	7.8kW	230 VAC	modular standard contactor	2NC	3
ESC440	40A	7.8kW	230 VAC	modular standard contactor	4NO	3
ESC442	40A	7.8kW	230 VAC	modular standard contactor	2NO+2NC	3
ESC263	63A	10kW	230 VAC	modular standard contactor	2NO	3
ERC263*	63A	10kW	230 VAC	modular standard contactor	2NO	3
ESC463	63A	10kW	230 VAC	modular standard contactor	4NO	3
ESC464	63A	10kW	230 VAC	modular standard contactor	4NC	3
ESC465	63A	10kW	230 VAC	modular standard contactor	2NO+2NC	3

Modular contactors with “low noise” coil

- No humming while energised / low switching noise

12 VDC modular contactors

ERL625SDC*	25A	–	12 VDC	low noise modular contactor	2NO	1
ERL425SDC*	25A	2.6kW	12 VDC	low noise modular contactor	4NO	2
ESL440S	40A	7.8kW	12 VDC	low noise modular contactor	4NO	3
ESL463S	63A	10kW	12 VDC	low noise modular contactor	4NO	3

24 VDC modular contactors

ERD225SDC*	25A	–	24 VDC	low noise modular contactor	2NO	1
ESD425SDC*	25A	2.6kW	24 VDC	low noise modular contactor	4NO	2
ESD440S	40A	7.8kW	24 VDC	low noise modular contactor	4NO	3
ESD463S	63A	10kW	24 VDC	low noise modular contactor	4NO	3

230 VAC modular contactors

ERC225S*	25A	–	230 VAC	low noise modular contactor	2NO	1
ERC425S*	25A	2.6kW	230 VAC	low noise modular contactor	4NO	2
ESC440S	40A	7.8kW	230 VAC	low noise modular contactor	4NO	3
ESC463S	63A	10kW	230 VAC	low noise modular contactor	4NO	3

* With manual override control

Contactors accessories

Auxiliary contact for all above contactors (not compatible with 1 module low noise contactors)

ESC080	1th 6A	–	–	clip-on auxiliary contact	1NO+1NC	0.5
LZ060	heat dissipation insert for mounting between contactors					0.5

To avoid overheating of contactors when installed side by side, insert a heat dissipation module between contactors

Modular stepping relays

EPN515	16A	–	230 VAC	modular stepping relay	1NO+1NC	1
EPN518	16A	–	24 VAC	modular stepping relay	1NO+1NC	1
EPN503	16A	–	24 VDC	modular stepping relay	1NO+1NC	1
EPN519	16A	–	12 VAC	modular stepping relay	1NO+1NC	1

Auxiliary for above stepping relays

EPN051	1th 6A	–	–	clip-on auxiliary contact	1NO+1NC	0.5
EPN053	1th 6A	–	–	impulse converter for maintained contact	1 ch/over	0.5