



NH000



NH1



NH2



NH3

Knife type (NH) fuse-links gG class for general use. High breaking capacity intended for protection of power lines and equipment against overloads and short-circuits. Ceramic body with high withstand to internal pressure and thermal shock, offering high breaking capacity. Manufactured according to IEC/EN60269 and VDE0636 standards and comply with RoHS directive.

Standards: IEC/EN 60269-1, IEC/EN 60269-2, DIN 43620

type	rated current	rated voltage	breaking capacity	fuse size	class	description
gG NH HRC fuse links 500V <i>top indicator</i>						
<ul style="list-style-type: none"> • gG class for use as general protection against overloads and short circuits • For protection of cables, power lines and equipment • Fusing indicator on top of fuse link 						
381010	6A	500V	120kA	NH000	gG	DIN HRC fuse link
381015	10A	500V	120kA	NH000	gG	DIN HRC fuse link
381020	16A	500V	120kA	NH000	gG	DIN HRC fuse link
381025	20A	500V	120kA	NH000	gG	DIN HRC fuse link
381030	25A	500V	120kA	NH000	gG	DIN HRC fuse link
381035	32A	500V	120kA	NH000	gG	DIN HRC fuse link
381045	40A	500V	120kA	NH000	gG	DIN HRC fuse link
381050	50A	500V	120kA	NH000	gG	DIN HRC fuse link
381055	63A	500V	120kA	NH000	gG	DIN HRC fuse link
381060	80A	500V	120kA	NH000	gG	DIN HRC fuse link
381065	100A	500V	120kA	NH000	gG	DIN HRC fuse link
381070	125A	500V	120kA	NH00	gG	DIN HRC fuse link
381075	160A	500V	120kA	NH00	gG	DIN HRC fuse link
381255	160A	500V	120kA	C1	gG	DIN HRC fuse link
381260	200A	500V	120kA	NH1	gG	DIN HRC fuse link
381270	250A	500V	120kA	NH1	gG	DIN HRC fuse link
381280	315A	500V	120kA	NH1	gG	DIN HRC fuse link
381285	355A	500V	120kA	NH1	gG	DIN HRC fuse link
381370	315A	500V	120kA	NH2	gG	DIN HRC fuse link
381375	355A	500V	120kA	NH2	gG	DIN HRC fuse link
381380	400A	500V	120kA	NH2	gG	DIN HRC fuse link
381390	500A	500V	120kA	NH2	gG	DIN HRC fuse link
381465	500A	500V	120kA	NH3	gG	DIN HRC fuse link
381470	630A	500V	120kA	NH3	gG	DIN HRC fuse link
381475	800A	500V	120kA	NH3	gG	DIN HRC fuse link
381525	800A	500V	120kA	NH4	gG	DIN HRC fuse link
381530	1000A	500V	120kA	NH4	gG	DIN HRC fuse link
381535	1250A	500V	120kA	NH4	gG	DIN HRC fuse link

gG NH HRC fuse links 690V <i>top indicator</i>						
382010	6A	690V	80kA	NH000	gG	DIN HRC fuse link
382015	10A	690V	80kA	NH000	gG	DIN HRC fuse link
382020	16A	690V	80kA	NH000	gG	DIN HRC fuse link
382025	20A	690V	80kA	NH000	gG	DIN HRC fuse link
382030	25A	690V	80kA	NH000	gG	DIN HRC fuse link
382035	32A	690V	80kA	NH000	gG	DIN HRC fuse link
382045	40A	690V	80kA	NH000	gG	DIN HRC fuse link
382050	50A	690V	80kA	NH00	gG	DIN HRC fuse link
382055	63A	690V	80kA	NH00	gG	DIN HRC fuse link
382060	80A	690V	80kA	NH00	gG	DIN HRC fuse link
382065	100A	690V	80kA	NH00	gG	DIN HRC fuse link
382250	125A	690V	80kA	NH1	gG	DIN HRC fuse link
382255	160A	690V	80kA	NH1	gG	DIN HRC fuse link
382260	200A	690V	80kA	NH1	gG	DIN HRC fuse link
382360	250A	690V	80kA	NH2	gG	DIN HRC fuse link
382370	315A	690V	80kA	NH2	gG	DIN HRC fuse link
382450	355A	690V	80kA	NH3	gG	DIN HRC fuse link
382455	400A	690V	80kA	NH3	gG	DIN HRC fuse link
382465	500A	690V	80kA	NH3	gG	DIN HRC fuse link
382520	630A	690V	80kA	NH4	gG	DIN HRC fuse link
382525	800A	690V	80kA	NH4	gG	DIN HRC fuse link

Fuse bases and accessories (see B-41)