



PSL1M...



PSL1...



PSL3...

**DIN rail mount power supplies**

- Modular DIN rail mounting (*aligns with standard MCB's with 45 mm cutout*)
- Rated voltage 12 VDC or 24 VDC
- High efficiency up to 89%
- Adjustable output voltage

type	input voltage	output voltage	rated load		dimensions (mm)		
			(A)	(W)	(H)	(W)	(D)

- Protection:
- short circuit
  - overvoltage
  - input voltage peaks

**Single-phase 100 - 240 VAC (*insulated modular housing*)**

<b>PSL1M02412</b>	90 - 264 VAC	12 VDC	2	24	96	35	56
<b>PSL1M03312</b>	90 - 264 VAC	12 VDC	2.75	33	96	53	56
<b>PSL1M05412</b>	90 - 264 VAC	12 VDC	4.5	54	96	71	56
<b>PSL1M07212</b>	90 - 264 VAC	12 VDC	6	72	96	90	56
<b>PSL1M02424</b>	90 - 264 VAC	24 VDC	1	24	96	35	56
<b>PSL1M03624</b>	90 - 264 VAC	24 VDC	1.5	36	96	53	56
<b>PSL1M06024</b>	90 - 264 VAC	24 VDC	2.5	60	96	71	56
<b>PSL1M10024</b>	90 - 264 VAC	24 VDC	4.2	100	96	90	56

**DIN rail mounting (IEC/EN 60715)**

- Rated voltage 24 VDC
- High efficiency up to 92%
- Adjustable output voltage

**Single phase (90 - 264 VAC)**

<b>PSL112024</b>	90 - 264 VAC	24 VDC	5	120	124	64	124
<b>PSL124024</b>	90 - 264 VAC	24 VDC	10	240	124	84	124
<b>PSL130024</b>	90 - 264 VAC	24 VDC	12.5	300	124	84	124

**Three phase (340 - 575 VAC)**

<b>PSL312024</b>	340 - 575 VAC	24 VDC	5	120	124	74	119
<b>PSL324024</b>	340 - 575 VAC	24 VDC	10	240	124	89	119
<b>PSL348024</b>	340 - 575 VAC	24 VDC	20	480	124	150	119