

new



086001-0-2



CENC 4



CENC 16



CENC 35



086105-0-4



086105-9-2



084551-1-4

CENC universal clamping yokes slide onto busbars 6 x 6 mm and 3 x 10 mm, providing a simple solution for purpose made earth or neutral busbar termination. Simply slide the required number of connection terminals onto the bar, mount the bar with the NES universal mounting support.

type	rated current	cable size mm ²	description	designation
------	---------------	----------------------------	-------------	-------------

NES Insulated universal support for 6 x 6 and 10 x 3 mm busbars

086001-0-2 – universal support for 6 x 6 and 10 x 3 mm busbars

Copper bars for above

GI06006.1 6 x 6 mm solid copper bar to accommodate CENC terminals (*below*)
GI03010.1 10 x 3 mm solid copper bar to accommodate CENC terminals (*below*)

CENC conductor connection terminals

CENC terminals slide onto 6 x 6 mm or 10 x 3 mm copper busbars to make up phase/neutral or earth bars with reliable cable clamping termination

CENC 4 - 4 mm² clamping yoke (accepts max conductor 10 mm²)

086006-0-4	41A	1 - 10 mm ²	slide-on conductor connection terminals	Line	
086006-1-4	41A	1 - 10 mm ²	slide-on conductor connection terminals	Neutral	
086006-2-4	41A	1 - 10 mm ²	slide-on conductor connection terminals	Earth	

CENC 16 - 16 mm² clamping yoke

086106-0-4	76A	2.5 - 16 mm ²	slide-on conductor connection terminals	Line	
086106-1-4	76A	2.5 - 16 mm ²	slide-on conductor connection terminals	Neutral	
086106-2-4	76A	2.5 - 16 mm ²	slide-on conductor connection terminals	Earth	

CENC 35 - 35 mm² clamping yoke

086306-0-4	125A	4 - 35 mm ²	slide-on conductor connection terminals	Line	
086306-1-4	125A	4 - 35 mm ²	slide-on conductor connection terminals	Neutral	
086306-2-4	125A	4 - 35 mm ²	slide-on conductor connection terminals	Earth	

SSAK conductor-connection terminals 690V DIN EN 60947-7-1

Fastens directly onto busbar (*max. 10 mm thick*) and provides 2 x outgoing cable terminals

- For direct cable connection to copper bars 3 - 10 mm thick

Insulated conductor connection terminals (H) 47.8 x (W) 15.5 x (D) 55.2

- All insulated, finger-safe PA6 (*self extinguishing, halogen free*)

086105-0-4	114A	2 x 1.5-16	busbar conductor connection terminal	Line	
086105-1-4	114A	2 x 1.5-16	busbar conductor connection terminal	Neutral	
086105-2-4	114A	2 x 1.5-16	busbar conductor connection terminal	Earth	
086105-3-4	114A	2 x 1.5-16	busbar conductor connection terminal	Line	

Uninsulated conductor connection terminals

086105-9-2 114A 2 x 1.5-16 (H) 42.1 x (W) 12 x (D) 32 – –

Feed in terminals (H) 27.1 x (W) 17.3 x (D) 24.7 mm (*without pin*)

Designed for ease of feed-in to common bridging busbars used with MCB's in distribution boards

- Universal, configurable for front or (*either*) side power feed
- Screw clamp termination ensuring touch safety

084551-1-4	–	50 mm ²	feed-in terminal short pin (<i>15 mm</i>)	grey	
084553-1-4	–	50 mm ²	feed-in terminal long pin (<i>29.5 mm</i>)	grey	