



Crimped ferrule



005649



**Ferrules / wire end sleeves**

- Material: Tin-plated copper (*min.thickness 3µ*) / polypropylene
- CSA certified (certificate 2110332) • DIN 46228 part 4, CSA C22.2 No. 65-93, 188-M1983

type	wire size mm <sup>2</sup>	colour	dimensions (mm)						pack qty
			L1	L2 <sup>1)</sup>	D1	S1	D2	D3	

**Ferrules with insulating collar**

- Supplied in mini bags on a strip, bags can be torn from strip individually

005606	0.50	white	13.5	8.0	1.1	0.15	2.4	-	0.30	100
005644	0.75	blue	14.0	8.0	1.3	0.15	2.7	-	0.30	100
005718	1.0	red	14.5	8.0	1.5	0.15	3.3	-	0.30	100
005738	1.0	red	16.5	10.0	1.5	0.15	3.3	-	0.30	100
005765	1.5	black	14.5	8.0	1.8	0.15	3.7	-	0.30	100
005791	1.5	black	16.5	10.0	1.8	0.15	3.7	-	0.30	100
005808	2.5	grey	15.0	8.0	2.3	0.15	4.1	-	0.30	100
005829	2.5	grey	17.0	10.0	2.3	0.15	4.1	-	0.30	100
005851	4.0	orange	18.0	10.0	2.9	0.20	4.7	-	0.30	100
007739*	4.0	grey	18.0	10.0	2.9	0.20	6.1	-	0.30	100
005871	6.0	green	20.0	12.0	3.6	0.20	6.1	-	0.30	100
005896	10.0	brown	21.0	12.0	4.6	0.20	7.4	-	0.30	100
005919	16.0	white	23.0	12.0	6.0	0.20	8.6	-	0.50	100
005950	25.0	black	29.0	16.0	7.5	0.20	10.9	-	0.50	50
005968	35.0	red	30.0	16.0	8.5	0.20	12.3	-	0.50	50
005980	50.0	blue	36.0	20.0	10.5	0.30	14.8	-	0.60	50
005988	70.0	yellow	37.0	20.0	12.7	0.40	15.8	-	0.60	25
005990	95.0	red	44.0	25.0	14.7	0.40	17.7	-	0.60	25
005915	120.0	blue	48.0	27.0	16.7	0.50	20.7	-	0.70	25

\* Accommodates wires with thicker insulation

**Ferrules with insulating collar belt strips (automatic crimping machine see page M-7)**

- Tape mounted supplied in type K box dispenser

005611	0.50	white	14.5	8.0	1.1	0.15	2.6	3.5	0.25	1000
005649	0.75	blue	14.5	8.0	1.3	0.15	2.8	3.6	0.25	1000
005720	1.0	red	14.5	8.0	1.5	0.15	3.0	3.9	0.30	1000
005767	1.5	black	14.5	8.0	1.8	0.15	3.4	4.2	0.30	1000
005813	2.5	grey	14.5	8.0	2.3	0.15	4.2	5.0	0.30	500

**Twin ferrules with insulating collar (accepts two cables)**

- Supplied in mini bags on a strip, bags can be torn from strip individually

005613	2 x 0.5	white	15.0	8.0	1.5	0.15	2.4	4.6	0.30	100
005653	2 x 0.75	blue	15.0	8.0	1.8	0.15	2.7	5.4	0.30	100
005722	2 x 1.0	red	15.0	8.0	2.1	0.15	3.3	5.3	0.30	100
005740	2 x 1.0	red	17.0	10.0	2.1	0.15	3.3	5.3	0.30	100
005770	2 x 1.5	black	16.0	8.0	2.3	0.15	3.5	6.5	0.30	100
005794	2 x 1.5	black	20.0	12.0	2.3	0.15	3.5	6.5	0.30	100
005816	2 x 2.5	grey	19.0	10.0	2.9	0.20	4.1	7.7	0.40	100
005853	2 x 4.0	orange	23.0	12.0	3.8	0.20	4.9	8.7	0.40	100
005873	2 x 6.0	green	25.0	14.0	4.9	0.20	6.1	9.9	0.40	100
005898	2 x 10.0	brown	26.0	14.0	6.5	0.20	7.1	12.9	0.50	100
005921	2 x 16.0	white	31.0	16.0	8.5	0.20	9.8	16.8	0.60	50

**Un-insulated ferrules (cord end / bootlace terminals)**

- Supplied in standard bulk pack quantity (size dependant)

type	wire size mm <sup>2</sup>	colour	dimensions (mm)				description	pack qty
			L2 <sup>1)</sup>	D1	D2	S1		
006010	0.50	-	10.0	1.0	2.5	0.15	un-insulated ferrules	1000
006015	0.75	-	10.0	1.2	2.3	0.15	un-insulated ferrules	1000
006022	1.0	-	10.0	1.4	2.5	0.15	un-insulated ferrules	1000
006031	1.5	-	10.0	1.7	2.8	0.15	un-insulated ferrules	1000
006045	2.5	-	12.0	2.2	3.4	0.15	un-insulated ferrules	1000
006053	4.0	-	12.0	2.8	4.0	0.2	un-insulated ferrules	1000
006060	6.0	-	12.0	3.5	4.7	0.2	un-insulated ferrules	1000
006068	10.0	-	12.0	4.5	5.8	0.2	un-insulated ferrules	1000
006079	16.0	-	12.0	5.8	7.5	0.2	un-insulated ferrules	250
006091	25.0	-	15.0	7.3	9.5	0.2	un-insulated ferrules	100
006098	35.0	-	18.0	8.3	11.0	0.2	un-insulated ferrules	100
006102	50.0	-	18.0	10.3	13.0	0.3	un-insulated ferrules	100
006107	70.0	-	25.0	12.5	15.0	0.4	un-insulated ferrules	100
006109	95.0	-	25.0	14.5	17.0	0.4	un-insulated ferrules	50
006075	120.0	-	32.0	16.5	19.0	0.5	un-insulated ferrules	50

<sup>1)</sup> Other lengths available on request

Available in smaller and larger wire sizes (up to 240 mm<sup>2</sup>)