



080210-0-4



080210-1-4



080210-2-4



080010-1-4

080010-0-4



082060-0-3

Main line/branch terminals

- 1 pole (4 x connections per pole) DIN rail mounting
- Rapid installation (stackable horizontally) clips together to add additional poles
- Extremely compact, all sides finger-safe
- Terminal body: brass (CuZn39Pb2) Housing: self-extinguishing, halogen free

type	rated current	terminal size (mm ²)		description	designation
		2 x main	2 x branch		

Hlak - main line/branch terminals

HLAK 25/16		1000 VAC/DC		(H) 52 x (W) 17.8 x (D) 49 mm		
080110-0-4	152A	2.5 - 25	1.5 - 16	rail mount terminals	Line	■
080110-1-4	152A	2.5 - 25	1.5 - 16	rail mount terminals	Neutral	■
080110-2-4	152A	2.5 - 25	1.5 - 16	rail mount terminals	Earth	■
HLAK 35/25		1000 VAC/DC		(H) 52 x (W) 22.2 x (D) 49 mm		
080210-0-4	202A	4 - 35	2.5 - 25	rail mount terminals	Line	■
080210-1-4	202A	4 - 35	2.5 - 25	rail mount terminals	Neutral	■
080210-2-4	202A	4 - 35	2.5 - 25	rail mount terminals	Earth	■
HLAK 70/50		1000 VAC/DC		(H) 60 x (W) 32.8 x (D) 53 mm		
080310-0-4	300A	10 - 70	6 - 50	rail mount terminals	Line	■
080310-1-4	300A	10 - 70	6 - 50	rail mount terminals	Neutral	■
080310-2-4	300A	10 - 70	6 - 50	rail mount terminals	Earth	■

Distribution blocks

- 1 pole (stackable horizontally) clips together to add additional poles
- Rapid horizontal installation on 35 mm DIN rail
- Extremely compact, all side finger-safe
- Terminal body: brass (CUZN39PB2) Housing: self-extinguishing, halogen free
- 690 VAC / 1000 VDC - DIN/EN 60947-7-1

type	rated current	feed-in terminals		output terminals mm ²					designation
		cable (mm ²)	busbar (mm)	1.5 - 10	1.5 - 16	2.5 - 25	4 - 35	6 - 50	

UVB - sub distribution blocks

UVB 100		690 VAC		(H) 55 x (W) 30 x (D) 49 mm				
080010-0-4	100A	2.5 - 25	-	6			Line	■
080010-1-4	100A	2.5 - 25	-	6			Neutral	■
080010-2-4	100A	2.5 - 25	-	6			Earth	■

PDB - power distribution Blocks

PDB 160		1000 VAC/DC		(H) 68 x (W) 33 x (D) 49 mm					
082040-0-3	164A	2.5 - 25	-	3	2		grey	■	
PDB 210		1000 VAC/DC		(H) 70 x (W) 37 x (D) 54 mm					
082050-0-3	214A	4 - 35	-		3	2	grey	■	
PDB 220		1000 VAC/DC		(H) 75 x (W) 41 x (D) 50 mm					
082060-0-3	215A	10 - 70	15 x 5		3	2	grey	■	
PDB 270		1000 VAC/DC		(H) 73 x (W) 52 x (D) 55 mm					
082070-0-3	270A	16 - 95	-			8	2	grey	■
PDB 400		1000 VAC/1500 VDC		(H) 94 x (W) 53 x (D) 67 mm					
082080-0-3	400A	35 - 120	24 x 10		4	3	2	grey	■
PDB 490		1000 VAC/1500 VDC		(H) 67 x (W) 52 x (D) 94 mm					
082090-0-3	490A	95 - 185	24 x 10		4	3	2	grey	■