



- Maximum electrical rating: 600V
- Operating temperature: 105°C
- Material: terminal: Copper (*tin plated*)
insulation: Vinyl (PVC)

type	colour	wire size mm ²	description	dimensions (mm)			pack qty
				d2	B	L	
Ring terminals							
R1-3V	red	0.5 - 1.5	insulated ring lug	3.2	5.5	16.7	100
R1-3.5MV	red	0.5 - 1.5	insulated ring lug	3.7	5.5	16.7	100
R1-4SV	red	0.5 - 1.5	insulated ring lug	4.3	6.6	19.6	100
R1-4LV	red	0.5 - 1.5	insulated ring lug	4.3	8.0	21.0	100
R1-5V	red	0.5 - 1.5	insulated ring lug	5.3	8.0	21.0	100
R1-6V	red	0.5 - 1.5	insulated ring lug	6.5	11.6	26.8	100
R1-8V	red	0.5 - 1.5	insulated ring lug	8.4	11.6	26.8	100
R1-10V	red	0.5 - 1.5	insulated ring lug	10.5	13.6	30.7	100
R1-12V	red	0.5 - 1.5	insulated ring lug	13	19.2	35.6	100
R2-3V	blue	1.5 - 2.5	insulated ring lug	3.2	6.4	17.5	100
R2-3.5MV	blue	1.5 - 2.5	insulated ring lug	3.7	6.4	17.5	100
R2-4SV	blue	1.5 - 2.5	insulated ring lug	4.3	6.6	19.5	100
R2-4LV	blue	1.5 - 2.5	insulated ring lug	4.3	8.5	22.0	100
R2-5SV	blue	1.5 - 2.5	insulated ring lug	5.3	8.5	22.0	100
R2-6V	blue	1.5 - 2.5	insulated ring lug	6.5	12.0	27.0	100
R2-8V	blue	1.5 - 2.5	insulated ring lug	8.4	12.0	27.0	100
R2-10V	blue	1.5 - 2.5	insulated ring lug	10.5	13.6	30.7	100
R2-12V	blue	1.5 - 2.5	insulated ring lug	13	19.2	35.6	100
R5-3SV	yellow	4.0 - 6.0	insulated ring lug	3.2	7.2	22.0	100
R5-3.5SV	yellow	4.0 - 6.0	insulated ring lug	3.7	7.2	22.0	100
R5-4SV	yellow	4.0 - 6.0	insulated ring lug	4.3	7.2	25.5	100
R5-4LV	yellow	4.0 - 6.0	insulated ring lug	4.3	9.5	25.5	100
R5-5V	yellow	4.0 - 6.0	insulated ring lug	5.3	9.5	25.5	100
R5-6V	yellow	4.0 - 6.0	insulated ring lug	6.5	12.0	29.0	100
R5-8V	yellow	4.0 - 6.0	insulated ring lug	8.4	15.0	33.7	100
R5-10V	yellow	4.0 - 6.0	insulated ring lug	10.5	15.0	33.7	100
R5-12V	yellow	4.0 - 6.0	insulated ring lug	13.0	9.2	38.1	100
Fork/spade terminals							
S1-3V	red	0.5 - 1.5	insulated fork lug	3.2	5.8	21.0	100
S1-3.5SV	red	0.5 - 1.5	insulated fork lug	3.7	5.8	21.0	100
S1-3.5MV	red	0.5 - 1.5	insulated fork lug	3.7	6.4	20.6	100
S1-4SV	red	0.5 - 1.5	insulated fork lug	4.3	6.4	20.6	100
S1-4MV	red	0.5 - 1.5	insulated fork lug	4.3	7.2	21.0	100
S1-5SV	red	0.5 - 1.5	insulated fork lug	5.3	8.0	21.0	100
S1-6SV	red	0.5 - 1.5	insulated fork lug	6.5	9.5	21.0	100
S2-3V	blue	1.5 - 2.5	insulated fork lug	3.2	5.8	21.0	100
S2-3.5SV	blue	1.5 - 2.5	insulated fork lug	3.7	5.8	21.0	100
S2-3.5MV	blue	1.5 - 2.5	insulated fork lug	3.7	6.4	21.0	100
S2-4SV	blue	1.5 - 2.5	insulated fork lug	4.3	6.4	21.0	100
S2-4LV	blue	1.5 - 2.5	insulated fork lug	4.3	8.5	22.0	100
S2-5SV	blue	1.5 - 2.5	insulated fork lug	5.3	8.5	22.0	100
S2-6SV	blue	1.5 - 2.5	insulated fork lug	6.5	9.5	22.0	100
S5-4SV	yellow	4.0 - 6.0	insulated fork lug	4.3	8.5	25.2	100
S5-5V	yellow	4.0 - 6.0	insulated fork lug	5.3	9.5	25.2	100
S5-6SV	yellow	4.0 - 6.0	insulated fork lug	6.5	9.5	25.2	100
Pin terminals							
PT1-10V	red	0.5 - 1.5	insulated pin lug	1.9	10.5	20.5	100
PT2-10V	blue	1.5 - 2.5	insulated pin lug	1.9	10.5	20.5	100
PT2-12V	blue	1.5 - 2.5	insulated pin lug	1.9	12.5	22.5	100
PT5-13V	yellow	4.0 - 6.0	insulated pin lug	2.8	13.7	26.2	100
Ferrule / butt connector							
BB1V	red	0.5 - 1.5	insulated ferrule	1.7	–	26.0	100
BB2V	blue	1.5 - 2.5	insulated ferrule	2.3	–	26.0	100
BB5V	yellow	4.0 - 6.0	insulated ferrule	2.3	–	26.0	100

