

|   | type                       | colour           | wire size<br>mm <sup>2</sup> | description                | dimensions (mm)          |      |      | pack<br>qty |     |
|---|----------------------------|------------------|------------------------------|----------------------------|--------------------------|------|------|-------------|-----|
|   |                            |                  |                              |                            | d2                       | B    | L    |             |     |
| <b>Flat-blade terminal</b>  |                            |                  |                              |                            |                          |      |      |             |     |
|   | <b>BT1-10V</b>             | red              | 0.5 - 1.5                    | insulated flat blade lug   | 2.4                      | 10.7 | 20.7 | 100         |     |
|   | <b>BT1-14V</b>             | red              | 0.5 - 1.5                    | insulated flat blade lug   | 3                        | 14   | 24   | 100         |     |
|   | <b>BT1-18V</b>             | red              | 0.5 - 1.5                    | insulated flat blade lug   | 2.4                      | 18   | 28   | 100         |     |
|   | <b>BT2-10V</b>             | blue             | 1.5 - 2.5                    | insulated flat blade lug   | 2.4                      | 10.7 | 20.7 | 100         |     |
|   | <b>BT2-13V</b>             | blue             | 1.5 - 2.5                    | insulated flat blade lug   | 2.4                      | 13   | 23   | 100         |     |
|   | <b>BT2-18V</b>             | blue             | 1.5 - 2.5                    | insulated flat blade lug   | 2.4                      | 18   | 28   | 100         |     |
|   | <b>BT5-10V</b>             | yellow           | 4.0 - 6.0                    | insulated flat blade lug   | 2.8                      | 10   | 22.5 | 100         |     |
|   | <b>BT5-18V</b>             | yellow           | 4.0 - 6.0                    | insulated flat blade lug   | 3                        | 18   | 30.5 | 100         |     |
|   | <b>Hook-blade terminal</b> |                  |                              |                            |                          |      |      |             |     |
|   |                            | <b>LB1-3V</b>    | red                          | 0.5 - 1.5                  | insulated hook blade lug | 3.0  | 18.0 | 28.0        | 100 |
| <b>LB1-4.6V</b>   |                            | red              | 0.5 - 1.5                    | insulated hook blade lug   | 4.6                      | 18.0 | 28.0 | 100         |     |
| <b>LB2-3V</b>   |                            | blue             | 1.5 - 2.5                    | insulated hook blade lug   | 3.0                      | 18.0 | 28.0 | 100         |     |
| <b>LB2-4.6V</b>   |                            | blue             | 1.5 - 2.5                    | insulated hook blade lug   | 4.6                      | 18.0 | 28.0 | 100         |     |
| <b>LB5-3V</b>   |                            | yellow           | 4.0 - 6.0                    | insulated hook blade lug   | 3.0                      | 17.5 | 30.0 | 100         |     |
| <b>LB5-4.6V</b>   |                            | yellow           | 4.0 - 6.0                    | insulated hook blade lug   | 4.6                      | 17.5 | 30.0 | 100         |     |
| <b>Female disconnect terminals "push-on"</b>                      |                            |                  |                              |                            |                          |      |      |             |     |
|   |                            | <b>F1-2.8V/5</b> | red                          | 0.5 - 1.5                  | female disconnect        | 2.8  | 3.2  | 18.5        | 100 |
|   | <b>F1-2.8VD/5*</b>         | red              | 0.5 - 1.5                    | female disconnect          | 2.8                      | 3.2  | 18.5 | 100         |     |
|   | <b>F1-4.8V/5</b>           | red              | 0.5 - 1.5                    | female disconnect          | 4.8                      | 5.0  | 19.0 | 100         |     |
|   | <b>F1-4.8VD/5*</b>         | red              | 0.5 - 1.5                    | female disconnect          | 4.8                      | 5.0  | 19.0 | 100         |     |
|   | <b>F1-6.4V</b>             | red              | 0.5 - 1.5                    | female disconnect          | 6.4                      | 6.6  | 21.0 | 100         |     |
|   | <b>F1-6.4VF</b>            | red              | 0.5 - 1.5                    | fully insulated disconnect | 6.4                      | 6.6  | 22.0 | 100         |     |
|   | <b>F1-6.4VD*</b>           | red              | 0.5 - 1.5                    | female disconnect          | 6.4                      | 6.6  | 21.0 | 100         |     |
|   | <b>F1-6.4VQD*</b>          | red              | 0.5 - 1.5                    | fully insulated disconnect | 6.4                      | 6.6  | 21.5 | 100         |     |
|   | <b>F2-2.8VD/5*</b>         | blue             | 1.5 - 2.5                    | female disconnect          | 2.8                      | 3.2  | 18.5 | 100         |     |
|   | <b>F2-4.8V/5</b>           | blue             | 1.5 - 2.5                    | female disconnect          | 4.8                      | 5.0  | 19.0 | 100         |     |
|   | <b>F2-4.8VD/5*</b>         | blue             | 1.5 - 2.5                    | female disconnect          | 4.8                      | 5.0  | 19.0 | 100         |     |
|   | <b>F2-6.4V</b>             | blue             | 1.5 - 2.5                    | female disconnect          | 6.4                      | 6.6  | 21.0 | 100         |     |
|   | <b>F2-6.4VF</b>            | blue             | 1.5 - 2.5                    | fully insulated disconnect | 6.4                      | 6.6  | 22.0 | 100         |     |
|   | <b>F2-6.4VD*</b>           | blue             | 1.5 - 2.5                    | female disconnect          | 6.4                      | 6.6  | 21.0 | 100         |     |
|   | <b>F2-6.4VQD*</b>          | blue             | 1.5 - 2.5                    | fully insulated disconnect | 6.4                      | 6.6  | 21.5 | 100         |     |
|   | <b>F2-8V</b>               | blue             | 1.5 - 2.5                    | female disconnect          | 8.0                      | 8.4  | 24.0 | 100         |     |
|   | <b>F2-8VD*</b>             | blue             | 1.5 - 2.5                    | female disconnect          | 8.0                      | 8.4  | 24.0 | 100         |     |
|   | <b>F5-6.4V</b>             | yellow           | 4.0 - 6.0                    | female disconnect          | 6.4                      | 6.6  | 23.5 | 100         |     |
|   | <b>F5-6.4VD*</b>           | yellow           | 4.0 - 6.0                    | female disconnect          | 6.4                      | 6.6  | 23.5 | 100         |     |
|   | <b>F5-6.4VQD*</b>          | yellow           | 4.0 - 6.0                    | fully insulated disconnect | 6.4                      | 6.6  | 24.5 | 100         |     |
| <b>F5-9.5V</b>  | yellow                     | 4.0 - 6.0        | female disconnect            | 9.5                        | 9.9                      | 28.5 | 100  |             |     |
| <b>F5-9.5VD*</b>  | yellow                     | 4.0 - 6.0        | female disconnect            | 9.5                        | 9.9                      | 28.5 | 100  |             |     |
| * Twin-grip crimp<br>■ Square entry / twin-grip / fully insulated |                            |                  |                              |                            |                          |      |      |             |     |
| <b>Male disconnect terminals "push-on"</b>                        |                            |                  |                              |                            |                          |      |      |             |     |
|   | <b>M1-2.8V/5</b>           | red              | 0.5 - 1.5                    | male disconnect            | —                        | 2.8  | 19.2 | 100         |     |
|   | <b>M1-2.8VD/5*</b>         | red              | 0.5 - 1.5                    | male disconnect            | —                        | 2.8  | 19.2 | 100         |     |
|   | <b>M1-4.8V/5</b>           | red              | 0.5 - 1.5                    | male disconnect            | —                        | 4.8  | 19.2 | 100         |     |
|   | <b>M1-4.8VD/5*</b>         | red              | 0.5 - 1.5                    | male disconnect            | —                        | 4.8  | 19.2 | 100         |     |
|   | <b>M1-6.4V</b>             | red              | 0.5 - 1.5                    | male disconnect            | —                        | 6.4  | 21.2 | 100         |     |
|   | <b>M1-6.4VD*</b>           | red              | 0.5 - 1.5                    | male disconnect            | —                        | 6.4  | 21.2 | 100         |     |
|   | <b>M2-2.8V/5</b>           | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 2.8  | 19.2 | 100         |     |
|   | <b>M2-2.8VD/5*</b>         | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 2.8  | 19.2 | 100         |     |
|   | <b>M2-4.8V/5</b>           | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 4.8  | 19.2 | 100         |     |
|   | <b>M2-4.8VD/5*</b>         | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 4.8  | 19.2 | 100         |     |
|   | <b>M2-6.4V</b>             | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 4.8  | 21.2 | 100         |     |
|   | <b>M2-6.4VD*</b>           | blue             | 1.5 - 2.5                    | male disconnect            | —                        | 4.8  | 21.2 | 100         |     |
|   | <b>M5-6.4V</b>             | yellow           | 4.0 - 6.0                    | male disconnect            | —                        | 6.4  | 23.2 | 100         |     |
|   | <b>M5-6.4VD*</b>           | yellow           | 4.0 - 6.0                    | male disconnect            | —                        | 6.4  | 23.7 | 100         |     |
|   | * Twin-grip crimp          |                  |                              |                            |                          |      |      |             |     |