

	type	colour	wire size mm ²	description	dimensions (mm)			pack qty	
					d2	B	L		
	Piggy back disconnect terminals "push-on"								
	PB1-6.4V	red		0.5 - 1.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB1-6.4VD*	red		0.5 - 1.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB2-6.4V	blue		1.5 - 2.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB2-6.4VD*	blue		1.5 - 2.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB5-6.4V	yellow		4.0 - 6.0	piggy-back disconnect	6.4	6.6	23.5	100
	PB5-6.4VD*	yellow		4.0 - 6.0	piggy-back disconnect	6.4	6.6	23.5	100
	<i>* Twin-grip crimp</i>								
	Male bullet disconnecter								
	BD1-4V	red		0.5 - 1.5	male bullet disconnect	–	4.0	21.0	100
	BD1-4VD*	red		0.5 - 1.5	male bullet disconnect	–	4.0	21.0	100
	BD2-5V	blue		1.5 - 2.5	male bullet disconnect	–	5.0	21.0	100
BD2-5VD*	blue		1.5 - 2.5	male bullet disconnect	–	5.0	21.0	100	
BD5-5V	yellow		4.0 - 6.0	male bullet disconnect	–	5.0	23.0	100	
BD5-5VD*	yellow		4.0 - 6.0	male bullet disconnect	–	5.0	23.0	100	
<i>* Twin-grip crimp</i>									
Female bullet disconnecter									
RE1-4VF	red		0.5 - 1.5	female bullet disconnect	–	4.0	22.0	100	
RE1-4VFD*	red		0.5 - 1.5	female bullet disconnect	–	4.0	22.5	100	
RE2-5VF	blue		1.5 - 2.5	female bullet disconnect	–	5.0	23.5	100	
RE2-5VFD*	blue		1.5 - 2.5	female bullet disconnect	–	5.0	23.5	100	
RE5-5VF	yellow		4.0 - 6.0	female bullet disconnect	–	5.0	25.5	100	
RE5-5VFD*	yellow		4.0 - 6.0	female bullet disconnect	–	5.0	25.0	100	
<i>* Twin-grip crimp</i>									
Quick-splice connectors									
SP1	red		0.5 - 1.5	quick-splice connector	–	20.0	26.8	100	
SP2	blue		1.5 - 2.5	quick-splice connector	–	20.0	26.8	100	
SP5	yellow		4.0 - 6.0	quick-splice connector	–	20.0	35.0	100	
Insulated cord-end (boot lace) terminals									
CE007508F	blue		0.75	cord-end terminal	1.2	14.0	8.0	500	
CE010010F	red		1.0	cord-end terminal	1.4	16.0	10.0	500	
CE015010F	black		1.5	cord-end terminal	1.7	16.0	10.0	500	
CE025012F	grey		2.5	cord-end terminal	2.2	18.0	12.0	500	
CE040012F	orange		4.0	cord-end terminal	2.8	20.0	12.0	500	
CE060012F	green		6.0	cord-end terminal	3.5	20.0	12.0	500	
CE100012F	brown		10.0	cord-end terminal	4.5	22.0	12.0	500	
CE160012F	ivory		16.0	cord-end terminal	5.8	24.0	12.0	500	
CE250016F	black		25.0	cord-end terminal	7.3	30.0	16.0	500	
Crimping tools for pre-insulated terminals									
<ul style="list-style-type: none"> • Crimping profiles for different wire cross-sections (red/blue/yellow) • With ratchet closing control 									
JSL 1305-1	universal crimping tool for: red / blue / yellow pre-insulated terminals								
Crimpfit IT6L	universal high quality "made in Germany" crimping tool for pre-insulated terminals								
<p>JSL 1305-1</p>									