

	type	colour	wire size mm ²	description	dimensions (mm)			pack qty
					d2	B	L	
	Piggy back disconnect terminals "push-on"							
	PB1-6.4V	red	0.5 - 1.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB1-6.4VD*	red	0.5 - 1.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB2-6.4V	blue	1.5 - 2.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB2-6.4VD*	blue	1.5 - 2.5	piggy-back disconnect	6.4	6.6	21.0	100
	PB5-6.4V	yellow	4.0 - 6.0	piggy-back disconnect	6.4	6.6	23.5	100
	PB5-6.4VD*	yellow	4.0 - 6.0	piggy-back disconnect	6.4	6.6	23.5	100
	<i>* Twin-grip crimp</i>							
	Male bullet disconnecter							
	BD1-4V	red	0.5 - 1.5	male bullet disconnect	–	4.0	21.0	100
BD1-4VD*	red	0.5 - 1.5	male bullet disconnect	–	4.0	21.0	100	
BD2-5V	blue	1.5 - 2.5	male bullet disconnect	–	5.0	21.0	100	
BD2-5VD*	blue	1.5 - 2.5	male bullet disconnect	–	5.0	21.0	100	
BD5-5V	yellow	4.0 - 6.0	male bullet disconnect	–	5.0	23.0	100	
BD5-5VD*	yellow	4.0 - 6.0	male bullet disconnect	–	5.0	23.0	100	
<i>* Twin-grip crimp</i>								
Female bullet disconnecter								
RE1-4VF	red	0.5 - 1.5	female bullet disconnect	–	4.0	22.0	100	
RE1-4VFD*	red	0.5 - 1.5	female bullet disconnect	–	4.0	22.5	100	
RE2-5VF	blue	1.5 - 2.5	female bullet disconnect	–	5.0	23.5	100	
RE2-5VFD*	blue	1.5 - 2.5	female bullet disconnect	–	5.0	23.5	100	
RE5-5VF	yellow	4.0 - 6.0	female bullet disconnect	–	5.0	25.5	100	
RE5-5VFD*	yellow	4.0 - 6.0	female bullet disconnect	–	5.0	25.0	100	
<i>* Twin-grip crimp</i>								
Quick-splice connectors								
SP1	red	0.5 - 1.5	quick-splice connector	–	20.0	26.8	100	
SP2	blue	1.5 - 2.5	quick-splice connector	–	20.0	26.8	100	
SP5	yellow	4.0 - 6.0	quick-splice connector	–	20.0	35.0	100	
	Insulated cord-end (boot lace) terminals							
	CE007508F	blue	0.75	cord-end terminal	1.2	14.0	8.0	500
	CE010010F	red	1.0	cord-end terminal	1.4	16.0	10.0	500
	CE015010F	black	1.5	cord-end terminal	1.7	16.0	10.0	500
	CE025012F	grey	2.5	cord-end terminal	2.2	18.0	12.0	500
	CE040012F	orange	4.0	cord-end terminal	2.8	20.0	12.0	500
	CE060012F	green	6.0	cord-end terminal	3.5	20.0	12.0	500
	CE100012F	brown	10.0	cord-end terminal	4.5	22.0	12.0	500
	CE160012F	ivory	16.0	cord-end terminal	5.8	24.0	12.0	500
	CE250016F	black	25.0	cord-end terminal	7.3	30.0	16.0	500
Category-M								
Crimping tools for pre-insulated terminals								
<ul style="list-style-type: none"> • Crimping profiles for different wire cross-sections (red/blue/yellow) • With ratchet closing control 								
JSL 1305-1	universal crimping tool for: red / blue / yellow pre-insulated terminals							
Crimpfit IT6L	universal high quality "made in Germany" crimping tool for pre-insulated terminals							

see page
M-3 for
info