



2232...



2234...



02235



192100240000

**Modular contactors 25A**

- Modular DIN rail mount
- Auto - On - Off selector
- Continuous duty coils and contacts
- AC/DC silent coil (*with varistor protection*)
- Mechanical flag and LED indicators as standard
- Clip-on auxiliary contact module available (1NO+1NC or 2NO)
- Protective separation (*reinforced insulation*) between coil and contacts

type	rated power		description	modules width in 17.5 mm	contact configuration	coil voltage AC/DC
	AC-1 (A)	AC-3 kW (230V)				
<b>2 pole modular contactor</b>			<b>25A</b>	<b>(H) 89 x (W) 17.5 (D) 61 mm</b>		

- Compact (*one module wide*) 17.5 mm

<b>223200124340</b>	25A	1.0 kW *	modular contactor	1	2 NO	12V
<b>223200244340</b>	25A	1.0 kW *	modular contactor	1	2 NO	24V
<b>223200484340</b>	25A	1.0 kW *	modular contactor	1	2 NO	48V
<b>223202304340</b>	25A	1.0 kW *	modular contactor	1	2 NO	230V
<b>223200124440</b>	25A	1.0 kW *	modular contactor	1	2 NC	12V
<b>223200244440</b>	25A	1.0 kW *	modular contactor	1	2 NC	24V
<b>223202304440</b>	25A	1.0 kW *	modular contactor	1	2 NC	230V
<b>223200124540</b>	25A	1.0 kW *	modular contactor	1	1NO + 1NC	12V
<b>223200244540</b>	25A	1.0 kW *	modular contactor	1	1NO + 1NC	24V
<b>223200484540</b>	25A	1.0 kW *	modular contactor	1	1NO + 1NC	48V
<b>223202304540</b>	25A	1.0 kW *	modular contactor	1	1NO + 1NC	230V

\* Single phase motor rating 230 VAC

<b>4 pole modular contactor</b>			<b>25A</b>	<b>(H) 89 x (W) 35 (D) 61 mm</b>		
---------------------------------	--	--	------------	----------------------------------	--	--

type	rated power		description	modules width in 17.5 mm	contact configuration	coil voltage AC/DC
	AC-1 (A)	AC-3 kW (400V)				
• Compact ( <i>two modules wide</i> ) 35 mm						

- Compact (*two modules wide*) 35 mm

<b>223400124340</b>	25A	4.0 kW	modular contactor	2	4 NO	12V
<b>223400244340</b>	25A	4.0 kW	modular contactor	2	4 NO	24V
<b>223402304340</b>	25A	4.0 kW	modular contactor	2	4 NO	230V
<b>223400124740</b>	25A	4.0 kW	modular contactor	2	3NO + 1NC	12V
<b>223400244740</b>	25A	4.0 kW	modular contactor	2	3NO + 1NC	24V
<b>223402304740</b>	25A	4.0 kW	modular contactor	2	3NO + 1NC	230V
<b>223400124640</b>	25A	4.0 kW	modular contactor	2	2NO + 2NC	12V
<b>223400244640</b>	25A	4.0 kW	modular contactor	2	2NO + 2NC	24V
<b>223402304640</b>	25A	4.0 kW	modular contactor	2	2NO + 2NC	230V

**Accessories for above contactors**

Clip-on auxiliaries for above contactors (H) 84 x (W) 8.8 (D) 61 mm

<b>02235</b>	6A	clip-on auxiliary contact block	0.5	1NO + 1NC		
<b>02233</b>	6A	clip-on auxiliary contact block	0.5	2 NO		
<b>02218</b>	8-way	jumper link for 2 pole contactors	1	17.5 mm	blue	
<b>02226</b>	6-way	jumper link for 4 pole contactors	2	35 mm	blue	
<b>02001</b>	adaptor	chassis mounting adaptor	1	17.5 mm		
<b>01101</b>	adaptor	chassis mounting adaptor	2	35 mm		
<b>02209</b>	separator	rail mounting contactor separator	0.5	9 mm		
<b>46392IPS</b>	sheet of (48) marking tags ( <i>mounts directly onto contactor</i> )					2232/4

<b>19 series modular DIN rail mount relay</b>			<b>(H) 84 x (W) 11.2 (D) 57 mm</b>			
---	--	--	------------------------------------	--	--	--

- 3 function selector switch
  - Auto: Works as a monostable relay
  - OFF: Relay permanently OFF
  - ON: Relay permanently ON

- Slimline (*11.2 mm wide*) modular relay
- LED indication - auto-off-on selector

<b>192100240000</b>	10A	slimline	modular relay		1 ch/over	24V
---------------------	-----	----------	---------------	--	-----------	-----