







Please note: Prices of copper products are based on the London Metal Exchange and will vary from time to time. Consult our sales department for the latest pricing before placing orders.



Solid copper bar



new



Solid copper bar (radius edge)

- ETP 99.90% min
- conductivity : 100 IACS

type	dimensions size(mm) W x D x length			current capacity	description	price
GI05020.3	20	5	3m	320A	solid copper bar	
GI05030.3	30	5	3m	450A	solid copper bar	
GI10030.3	30	10	3m	630A	solid copper bar	
GI10040.3	40	10	3m	850A	solid copper bar	
GI10050.3	50	10	3m	1000A	solid copper bar	
GI10060.3	60	10	3m	1250A	solid copper bar	
GI10080.3	80	10	3m	1500A	solid copper bar	
GI10100.3	100	10	3m	1800A	solid copper bar	

New "H" profile solid busbar 720mm²

New "H" profile permits Busbar systems with high current capacity (1600A) 720mm² in a very compact area (60mm) busbar centre spacing)
 • utilizing Wohner 01231 3 pole busbar supports.

GI01249	30"H" profile	2.4m	1600A	"H" profile solid busbar
----------------	---------------	------	-------	--------------------------

Small dimensioned solid bars (radius edge)

- electrolytic copper
- used with supports and clamping yokes to create earth/neutral bars for small distribution boards

GI106006.1	6	6	1m	80A	square copper bar
GI03010.1	10	3	1m	65A	flat copper bar

Threaded busbars (bolt/screws not supplied)

- electrolytic copper Cu-ETP 99.90%
- radius edge

type	dimensions size(mm) W x D x length			threaded hole DIA	distance apart (mm)	price
GI05015TH	15	5	1m	M6	25mm threaded bar	
GI05020TH	20	5	1m	M6	25mm threaded bar	
GI10030TH	30	10	2m	M8	25mm threaded bar	

Drum busbar insulators DMC

Simple busbar stand-off insulators with threaded socket top and bottom

Values	SM25	SM30	SM35	SM40	SM45	SM51	SM60	SM76
Tensile strength (kg)	220mm	260mm	280mm	300mm	300mm	470mm	700mm	700mm
Torque (kg)	2.8mm	3.8mm	4.8mm	4.8mm	4.8mm	9.5mm	15mm	19mm
Voltage withstand (kV)	6mm	8mm	10mm	12mm	12mm	15mm	20mm	25mm
Screw diameter (mm)	6mm	8mm	8mm	8mm	8mm	8mm	10mm	10mm

type	height	threaded socket dia	voltage withstand	description	price
SM25	25mm	6mm	6kV	busbar insulator	
SM30	30mm	8mm	8kV	busbar insulator	
SM35	35mm	8mm	10kV	busbar insulator	
SM40	40mm	8mm	12kV	busbar insulator	
SM45	45mm	8mm	12kV	busbar insulator	
SM51	51mm	8mm	15kV	busbar insulator	
SM60	60mm	10mm	20kV	busbar insulator	
SM76	76mm	10mm	25kV	busbar insulator	

Dimensions	SM25	SM30	SM35	SM40	SM45	SM51	SM60	SM76
A	25mm	30mm	35mm	40mm	45mm	51mm	60mm	76mm
B	23mm	26mm	28mm	34mm	28mm	29mm	34mm	36mm
C	27mm	32mm	32mm	40mm	37mm	36mm	47mm	50mm
D Ø	6mm	8mm	8mm	8mm	8mm	8mm	10mm	10mm
E	9mm	10mm	10mm	10mm	10mm	13mm	13mm	16mm
F	9mm	10mm	10mm	12mm	10mm	12mm	14mm	23mm