



Kwh meters / enclosures



EC370

new

type	current	operation	description	17.5mm width in	price
Three phase Kwh meter up to 6000A (connection via current transformer)					
<ul style="list-style-type: none"> • displays consumption of active energy • displays consumption of reactive energy • displays instantaneous power consumption • accuracy 1% • LED indication blinking according to consumption impulse output 1 pulse=100wH • back light LCD • fault indication (current sense not respected, phase order) • no polarity for CT connection • adapted to various networks (3ph with or without neutral, 230 or 400V between lines) • unlimited memory of measurement information 					
EC370	6000A	CT operated	three phase Kwh meter	4	



GD106A



GD110T



GZ04N

type	no. of ways	description	dimensions H x W x D	price
Surface shrouds IP30 (incorporates DIN rail profile - lead sealable)				
<ul style="list-style-type: none"> • incorporated labelling facility • hinge doors available (see below) 				
GD102B	2 way	IP30 surface mount shroud	160 x 55 x 82	
GD104B	4 way	IP30 surface mount shroud	180 x 110 x 82	
GD106B	6 way	IP30 surface mount shroud	180 x 146 x 82	
GD110B	10 way	IP30 surface mount shroud	180 x 218 x 82	
GP102T		transparent horizontally hinged door for	GD102	
GP104T		transparent horizontally hinged door for	GD104	
GP106T		transparent horizontally hinged door for	GD106	
GP110T		transparent horizontally hinged door for	GD110	
GZ104S		terminal support bracket (clip-in) for (GZ04E/N)	GD104	
GZ106S		terminal support bracket (clip-in) for (GZ04E/N)	GD106	
GZ110S		terminal support bracket (clip-in) for (GZ04E/N)	GD110	
GZ04E		insulated earth terminal (2 x 16 + 2 x 10 ²) clip onto bracket		
GZ04N		insulated neutral terminal (2 x 16 + 2 x 10 ²) clip onto bracket		



VU24D



VE212

Volta series exclusive flush mount boards IP41 (Class II)				
<ul style="list-style-type: none"> • high quality, aesthetically pleasing • sheet-metal front frame and door - robust wall tray • complete with fully insulated earth and neutral bars (quick connect) 				
VU12NR	12	flush mount distribution board	336 x 348 x 96	
VU24NR	24 (2x12)	flush mount distribution board	461 x 348 x 96	
VU36NR	36 (3x12)	flush mount distribution board	586 x 348 x 96	
VU48NR	48 (4x12)	flush mount distribution board	711 x 348 x 96	

Vector IP65 weatherproof surface mount (standard transparent door)				
<ul style="list-style-type: none"> • rear adjustment screws for mounting on uneven surfaces • can be connected side by side • knock-out cable entries top, bottom, sides • adjustable DIN rail depth (to accommodate MCCBs up to 160A) • supplied complete with earth and neutral terminals 				
VE103L	3 way	IP65 surface distribution board	111 x 175 x 93	
VE106L	6 way	IP65 surface distribution board	190 x 165 x 113	
VE110L	10 way	IP65 surface distribution board	210 x 237 x 114	
VE112L	12 way	IP65 surface distribution board	302 x 310 x 151	
VE118L	18 way	IP65 surface distribution board	302 x 418 x 151	
VE212L	24 way	IP65 surface distribution board	452 x 418 x 151	
VE218L	36 way	IP65 surface distribution board	602 x 418 x 151	
VE318L	54 way	IP65 surface distribution board	602 x 418 x 151	
VZ711		empty support for earth/neutral/phase terminals for Volta/Vector (see pg 73 for terminals)		