



Automatic changeover switches ATyS 250A - 3200A

type	AC-22A 400V(A)	description	dimensions (mm) H x W x D	price
------	-------------------	-------------	------------------------------	-------

ATyS 3 series motorised changeover switches

Mechanically interlocked, back to back mounted, load break switches. Their compact design guarantees position stability with high dynamic withstand electrically and mechanically interlocked.

- easily replaceable motor (without disconnection of power cables)
- incorporated auxiliaries for electrical interlocking
- manual override (handle supplied) permits direct manual operation
- remote operated via volt free contacts (pulsed or maintained)
- padlockable in "off" position



1523 3100

1523 3025	250A	3 pole motorised changeover switch	160 x 328 x 245
1523 3040	400A	3 pole motorised changeover switch	170 x 328 x 245
1523 3063	630A	3 pole motorised changeover switch	260 x 377 x 321
1523 3080	800A	3 pole motorised changeover switch	370 x 504 x 392
1523 3100	1000A	3 pole motorised changeover switch	370 x 504 x 392
1523 3120	1250A	3 pole motorised changeover switch	370 x 504 x 392
1523 3160	1600A	3 pole motorised changeover switch	380 x 596 x 392
1533 3200	2000A	3 pole motorised changeover switch	388 x 596 x 569
1533 3250	2500A	3 pole motorised changeover switch	388 x 596 x 569
1533 3320	3200A	3 pole motorised changeover switch	388 x 596 x 569

4 pole available on request

(3 pole price x 1.40)

Accessories for all changeover switches

Bridging bars to provide a common connection on either incoming or outgoing terminals



1523 3160

4109 3025	250A	3 pole bridging bar set for changeover switches	250A
4109 3039	400A	3 pole bridging bar set for changeover switches	400A
4109 3063	630A	3 pole bridging bar set for changeover switches	630/800A
4109 3120	1250A	3 pole bridging bar set for changeover switches	1250A
4109 3160	1600A	3 pole bridging bar set for changeover switches	1600A

1509 0001	mounting spaces (raise switch by 10mm) (2 pieces)	250-800A
1529 0012	door protective surround frame for switches	250-800A
1529 0080	door protective surround frame for switches	1000-1600A
1539 0080	door protective surround frame for switches	2000-3200A

Motorised load-break switches I-O 630-1600A

SIRCO motorised switches

- ideal contactor replacement for high current switching applications
- pulse controlled so is not energised continually (no coil burn-out)
- compact, reliable, robust AC-23A switching
- manual override facility (handle supplied)



4109 0080

type	AC-23A 415V(A)	AC-23A 400V(kW)	description	dimensions (mm) H x W x D	price
------	-------------------	--------------------	-------------	------------------------------	-------

3 pole switches

1915 3063	630A	280kW	3 p motorised switch	260 x 377 x 325
1915 3080	800A	450kW	3 p motorised switch	321 x 504 x 392
1915 3100	1000A	560kW	3 p motorised switch	321 x 504 x 392
1915 3120	1250A	710kW	3 p motorised switch	330 x 504 x 392
1915 3160	1600A	710kW	3 p motorised switch	288 x 596 x 392

4 pole switches

1915 4063	630A	280kW	4 p motorised switch	260 x 437 x 325
1915 4080	800A	450kW	4 p motorised switch	321 x 584 x 392
1915 4100	1000A	560kW	4 p motorised switch	321 x 584 x 392
1915 4120	1250A	710kW	4 p motorised switch	330 x 584 x 392
1915 4160	1600A	710kW	4 p motorised switch	288 x 716 x 392

Accessories

1509 0001	mounting spaces (raised switch by 10mm) (2 pieces)	250-630A
1529 0012	door protective surround frame for switches	250-630A
1529 0080	door protective surround frame for switches	800-1600A



1523 3100