

Industrial motor driven sirens								
type	supply voltage	dB @ 1m	description	IP	run duration on	run duration off	dimensions (Ø)	(H)
MICRO W10 series - Motor driven sirens								
Ideal choice for industrial applications, from general-purpose signalization to warning.								
• Can be installed vertically or horizontally								
42200	12 VDC	93	motor driven siren	IP42	(continuous)	84	80	
42202	24 VDC	93	motor driven siren	IP42	(continuous)	84	80	
42212	240 VAC	93	motor driven siren	IP42	(continuous)	90	129	
CELERE series - Motor driven sirens								
• Self-extinguishing PC body with high impact resistance								
• Motor protection thermal circuit breaker installed on CELERE and superCELERE versions.								
• Easy installation by means of the integrated fixing bracket - M12 cable gland								
mini-CELERE miniature electro-mechanical siren (300m)								
42006	12 VDC	101	motor driven siren	IP43	(continuous)	91	115	
42001	24 VAC/DC	101	motor driven siren	IP43	1 min. 10 min.	91	115	
42005	240 VAC/DC	101	motor driven siren	IP43	1 min. 10 min.	91	115	
CELERE mid sized electro-mechanical siren (500m)								
42026	12 VDC	110	motor driven siren	IP43	(continuous)	118	167	
42021	24 VAC/DC	110	motor driven siren	IP43	1 min. 10 min.	118	167	
42025	240 VAC/DC	110	motor driven siren	IP43	1 min. 10 min.	118	167	
super-CELERE large size electro-mechanical siren (1000m)								
42046	12 VDC	114	motor driven siren	IP43	(continuous)	140	186	
42047	24 VAC/DC	114	motor driven siren	IP43	(continuous)	140	186	
42045	240 VAC/DC	114	motor driven siren	IP43	1 min. 10 min.	140	186	
Electronic sirens								
SE4/29 series - Modular base mount sirens								
• Adjustable volume regulation and sound progression regulation								
• 5 selectable sound tones	- Continuos	1000 Hz						
	- Bi-tone	600/700 Hz						
	- Multi-tone	1000-1700 Hz						
	- Modulated	1000-1700 Hz						
	- Two-tone	440/560 Hz for evacuation						
50415	12 - 24 VAC/DC	97	electronic siren	IP30	(selectable)	100	90	
50418	240 VAC	97	electronic siren	IP30	(selectable)	100	90	
SE12 series - Electronic sirens (hinged mounting bracket)								
• Adjustable volume regulation and sound progression regulation								
• 32 different tones (selectable via dip-switches) frequency ranges 300/2850 Hz								
50424	12 - 24 VAC/DC	114	electronic siren	IP43	(selectable)	102	108	
50427	240 VAC	113	electronic siren	IP43	(selectable)	130	108	
SIR-TOUCH - Electronic siren super loud 120dB (IP68, IP69K)								
• Unique touch programming								
• 120 dB super load siren (6 programmable volume levels)								
• 64 different programmable sounds								
• M12 plug-in termination								
• Available with built-in LED light								
SIR-TOUCH Siren only								
90750	24 VDC	120	electronic siren	IP68	(selectable)	180	207	
90751	85 - 265 VAC	120	electronic siren	IP68	(selectable)	180	207	
SIR-TOUCH LED Siren and LED beacon (programmable for steady light, flashing light or off)								
90752	24 VDC	120	electronic siren	IP68	(selectable)	180	207	
90753	85 - 265 VAC	120	electronic siren	IP68	(selectable)	180	207	
Accessories for SIR-TOUCH siren								
90754	mount				swivel wall mount bracket for above siren			
90755	mount		SE 12		swivel base mount bracket for above siren			
120104-06-053	4 Pin female				M12 PUR cable for SIR-TOUCH termination		2 meter	
120104-06-061	4 Pin female				M12 PUR cable for SIR-TOUCH termination		5 meter	