



P40 series - Panel mount Ø41 mm signalling devices - (mounts through Ø30 mm hole)

With multifunctional technology, permitting different selectable signalling levels via independent electric contacts.

- 4 bright LEDs, Ø41 mm domed lens 360° light diffusion with maximized frontal performance
- Mounts through Ø30 mm hole - screw terminals (*internal depth max. 37 mm*)

| type | lens colour | dB @ 1m max | supply | description | dimensions (mm) | |
|------|-------------|-------------|--------|-------------|-----------------|------|
| | | | | | Ø | ext. |

P40 S - Multifunctional LED signalling panel beacon (IP65)

3 alarm levels: Steady - flashing - strobe (*selectable via electrical contacts*)

| | | | | | | |
|--------------|-------|---|----------------|-----------------------------|----|----|
| 91132 | amber | - | 12 - 24 VAC/DC | panel mnt signalling device | 41 | 46 |
| 91133 | red | - | 12 - 24 VAC/DC | panel mnt signalling device | 41 | 46 |
| 91134 | green | - | 12 - 24 VAC/DC | panel mnt signalling device | 41 | 46 |
| 91152 | amber | - | 48 - 240 VAC | panel mnt signalling device | 41 | 46 |
| 91153 | red | - | 48 - 240 VAC | panel mnt signalling device | 41 | 46 |
| 91154 | green | - | 48 - 240 VAC | panel mnt signalling device | 41 | 46 |

P40 A - Piezoelectric acoustic sounder - selectable continuous - intermittent sound

| | | | | | | |
|--------------|------|------|----------------|---------------------------|----|----|
| 91177 | grey | 85dB | 12 - 24 VAC/DC | panel mnt audible sounder | 41 | 34 |
| 91179 | grey | 85dB | 48 - 240 VAC | panel mnt audible sounder | 41 | 34 |

P40 A LED - Combination sounder and signal beacon (IP65)

3 alarm levels : Flashing only / flashing + intermittent sound / steady light + continuous sound

| | | | | | | |
|--------------|-------|------|----------------|--------------------------|----|----|
| 91182 | amber | 85dB | 12 - 24 VAC/DC | panel mnt sounder/beacon | 41 | 34 |
| 91183 | red | 85dB | 12 - 24 VAC/DC | panel mnt sounder/beacon | 41 | 34 |
| 91202 | amber | 85dB | 48 - 240 VAC | panel mnt sounder/beacon | 41 | 34 |
| 91203 | red | 85dB | 48 - 240 VAC | panel mnt sounder/beacon | 41 | 34 |

OVOLUX LED - Multifunctional LED signalling beacon (IP66)

- 4 light effects: Steady - single - double - triple flash (*selectable via dip-switches*)
- Bright LEDs, Ø76 mm domed lens 360° light diffusion with maximized frontal performance
- "R" version panel mount - through 1/2" NPT (22 mm) hole with (*provided*) lock ring

| | | | | | | |
|--------------|-------|---|----------------|-------------------------------|----|----|
| 38782 | amber | - | 12 - 24 VAC/DC | panel mount signalling device | 76 | 69 |
| 38783 | red | - | 12 - 24 VAC/DC | panel mount signalling device | 76 | 69 |
| 38784 | green | - | 12 - 24 VAC/DC | panel mount signalling device | 76 | 69 |
| 38792 | amber | - | 90 - 240 VAC | panel mount signalling device | 76 | 69 |
| 38793 | red | - | 90 - 240 VAC | panel mount signalling device | 76 | 69 |
| 38794 | green | - | 90 - 240 VAC | panel mount signalling device | 76 | 69 |

OVOLUX RGB - Multicolor steady light - LED beacon

- Multi-coloured: White, amber, red, yellow, green, magenta, blue (*7 colours in one beacon*)

| | | | | | | |
|--------------|-------|---|----------------|-------------------------------|----|----|
| 30107 | multi | - | 12 - 24 VAC/DC | panel mount signalling device | 76 | 69 |
| 30108 | multi | - | 90 - 240 VAC | panel mount signalling device | 76 | 69 |

OVOLUX mounting accessories

| | | | | | | |
|--------------|---------|--|--|--|--|--|
| 27697 | adaptor | for mounting Ovolux beacons onto a foot or wall mount base | | | | |
| 27762 | | surface mounting wall bracket for Ovolux (<i>requires 27697 adaptor</i>) | | | | |
| 27764 | | surface mount base with extended foot (100 mm) (<i>requires 27697 adaptor</i>) | | | | |

P50 series - Panel mount Ø50 mm LED signalling devices (IP68)

Multifunctional technology, permitting different selectable alarm levels via independent electric contacts. Illuminated dome (Ø50 mm) provides easy-to-see operator guidance and indication.

- Mounts through Ø22 mm standard pushbutton hole secured with (*provided*) locking ring
- 6 bright LEDs. Polycarbonate dome with 360° light-diffusion design
- **M12** 4 PIN connector (*See page K-27/28 for cable and connectors*)

P50 S - Multifunctional LED signalling panel beacon

- 7 different light effects (*steady, slow/fast flashing, double/triple flash, strobe, random flash*)

| | | | | | | |
|--------------|-------|---|----------------|-----------------------------|----|------|
| 91362 | amber | - | 12 - 24 VAC/DC | panel mnt signalling device | 50 | 26.5 |
| 91363 | red | - | 12 - 24 VAC/DC | panel mnt signalling device | 50 | 26.5 |
| 91364 | green | - | 12 - 24 VAC/DC | panel mnt signalling device | 50 | 26.5 |

P50 RGB - Multicolour LED panel beacon - Steady light with 7 different selectable colours

| | | | | | | |
|--------------|-------|---|----------------|--------------------------|----|------|
| 91378 | multi | - | 12 - 24 VAC/DC | multicoloured LED beacon | 50 | 26.5 |
|--------------|-------|---|----------------|--------------------------|----|------|

P50 A - Panel mount piezoelectric acoustic sounder

- 7 different types of alarm controllable via independent electric contacts.

| | | | | | | |
|--------------|------|------|----------------|---------------------------|----|------|
| 91367 | grey | 88dB | 12 - 24 VAC/DC | panel mnt audible sounder | 50 | 27.5 |
|--------------|------|------|----------------|---------------------------|----|------|

P50 A LED - Combination sounder and signal beacon

| | | | | | | |
|--------------|-------|------|----------------|--------------------------|----|------|
| 91382 | amber | 88dB | 12 - 24 VAC/DC | panel mnt sounder/beacon | 50 | 27.5 |
| 91383 | red | 88dB | 12 - 24 VAC/DC | panel mnt sounder/beacon | 50 | 27.5 |