

new



GAZ025



GAZM016EM



GAZM160EM



GAZS016EM

G... series enclosed switch disconnectors are supplied in robust, heavy duty enclosures in an IP65 execution. The enclosures incorporate a red/yellow operating handle mechanically interlocked with cover in the "ON" position and padlockable (3 padlocks) in the "OFF" position.

type	AC21A ≤ 690V		AC23A ≤ 415V		poles	description	dimensions (mm)		
							(H)	(W)	(D)
Plastic ABS enclosed isolators (IP65)									
GAZ016	16A	7.5kW	3 pole	enclosed load-break switch	160	100	120		
GAZ025	25A	11.0kW	3 pole	enclosed load-break switch	160	100	120		
GAZ032	32A	15.0kW	3 pole	enclosed load-break switch	160	100	120		
GAZ040EM	40A	18.5kW	3 pole	enclosed load-break switch	160	100	120		
GAZ063EM	63A	22.0kW	3 pole	enclosed load-break switch	160	100	120		
GAZ080EM	80A	45.0kW	3 pole	enclosed load-break switch	210	175	122		
GAZ125EM	125A	55.0kW	3 pole	enclosed load-break switch	210	175	122		
GAZ160EM	160A	55.0kW	3 pole	enclosed load-break switch	210	175	122		

For 4 pole - add attachable 4th pole (below) to above switches.

Empty ABS plastic enclosures only (with red/yellow handle and extension shaft)

GAZ1	empty enclosure with handle and extension shaft	160	100	97
GAZ2	empty enclosure with handle and extension shaft	210	175	99

Metal enclosed isolators (IP65)

GAZ series 16...160A

GAZM016EM	16A	7.5kW	3 pole	enclosed load-break switch	200	150	120
GAZM025EM	25A	11.0kW	3 pole	enclosed load-break switch	200	150	120
GAZM032EM	32A	15.0kW	3 pole	enclosed load-break switch	200	150	120
GAZM040EM	40A	18.5kW	3 pole	enclosed load-break switch	200	150	120
GAZM063EM	63A	22.0kW	3 pole	enclosed load-break switch	200	150	120
GAZM080EM	80A	45.0kW	3 pole	enclosed load-break switch	200	150	120
GAZM125EM	125A	55.0kW	3 pole	enclosed load-break switch	250	200	170
GAZM160EM	160A	55.0kW	3 pole	enclosed load-break switch	250	200	170

GLZ series 200...315A

GLZM0200EM	200A	110kW	3 pole	enclosed load-break switch	450	300	220
GLZM0250EM	250A	132kW	3 pole	enclosed load-break switch	450	300	220
GLZM0315EM	315A	140kW	3 pole	enclosed load-break switch	450	300	220

For 4 pole - add attachable 4th pole (below) to above switches.

Stainless steel (AISI 304) enclosed isolators (IP65)

GAZS016EM	16A	7.5kW	3 pole	enclosed load-break switch	200	150	120
GAZS025EM	25A	11.0kW	3 pole	enclosed load-break switch	200	150	120
GAZS032EM	32A	15.0kW	3 pole	enclosed load-break switch	200	150	120
GAZS040EM	40A	18.5kW	3 pole	enclosed load-break switch	200	150	120
GAZS063EM	63A	22.0kW	3 pole	enclosed load-break switch	200	150	120

For 4 pole - add attachable 4th pole (below) to above switches.

Attachable 4th pole for above switches

GAX42040A	40A	18.5kW	attachable 4th pole for above switches	GA016...40A
GAX42063SA	63A	22.0kW	attachable 4th pole for above switches	GA063SA
GAX42125A	125A	55.0kW	attachable 4th pole for above switches	GA063...125A
GAX42160A	160A	55.0kW	attachable 4th pole for above switches	GA160A
GAX41040A	40A	18.5kW	attachable early-make 4th pole for above	GA016...40A
GAX41125A	125A	55.0kW	attachable early-make 4th pole	GA063...125A
GLX420315	315A	132kW	attachable 4th pole for above switches	GL0160...315A