



Industrial protection HRC fuses

Rated voltage: 500 VAC
 Rated breaking capacity: 80 kA
 Standards specification: BS88-2, IEC 60269-2-1
 Fuse class: gG/Q1

type	rated current	BS88 ref.	rated voltage	breaking capacity	fixing centres	body dia. (mm)	type (GEC)
Off-set blade tag fuses (F1) body length 60 mm							
FGN 02A	2A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 04A	4A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 06A	6A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 10A	10A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 16A	16A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 20A	20A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 25A	25A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
FGN 32A	32A	A1/NP	500V	80kA	offset blade	14.2 mm	NS
Off-set bolted tag (A2) body length 86 mm							
FSA 02A	2A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 04A	4A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 06A	6A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 10A	10A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 16A	16A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 20A	20A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 25A	25A	A2	500V	80kA	73 mm	21.5 mm	TIA
FSA 32A	32A	A2	500V	80kA	73 mm	21.5 mm	TIA
Off-set bolted tag (A3) body length 90 mm							
FSS 40	40A	A3	500V	80kA	73 mm	21.5 mm	TIS
FSS 50	50A	A3	500V	80kA	73 mm	21.5 mm	TIS
FSS 63	63A	A3	500V	80kA	73 mm	21.5 mm	TIS
Off-set bolted tag (A4) body length 111 mm							
FSDCP 63	63A	A4	500V	80kA	94 mm	32 mm	TCP
FSDCP 80	80A	A4	500V	80kA	94 mm	32 mm	TCP
FSDCP 100	100A	A4	500V	80kA	94 mm	32 mm	TCP
Off-set bolted tag (A4) body length 111 mm							
FSFP 125	125A	A4a	500V	80kA	94 mm	39.5 mm	TFP
FSFP 160	160A	A4a	500V	80kA	94 mm	39.5 mm	TFP
FSFP 200	200A	A4a	500V	80kA	94 mm	39.5 mm	TFP
Central bolted tag (B2) body length 132 mm							
FSF 160	160A	B2	500V	80kA	111 mm	39.5 mm	TF
FSF 200	200A	B2	500V	80kA	111 mm	39.5 mm	TF
Central bolted tag (B3) body length 136 mm							
FSK 250	250A	B3	500V	120kA	111 mm	50.5 mm	TKF
FSK 315	315A	B3	500V	120kA	111 mm	50.5 mm	TKF
Central bolted tag (B4) body length 136 mm							
FMF 355	355A	B4	500V	80kA	111 mm	50.5 mm	TMF
FMF 400	400A	B4	500V	80kA	111 mm	50.5 mm	TMF
Central bolted tag (C2) body length 208 mm							
FTM 500	500A	C2	500V	80kA	133/184 mm	70.2 mm	TTM
FTM 600	600A	C2	500V	80kA	133/184 mm	70.2 mm	TTM