





P01157150



P01157151 + P01102134



## Chauvin Arnoux - PEL103 Power & Energy Loggers IP54 casing

Portable, advanced yet simple to use Power and Energy logger, designed for energy audits (ISO 50001 standard) or one-off measurements of the Power and Energy values in low-voltage electrical networks (1000 V CAT III)

PEL100 series Power and Energy loggers provide a complete solution to measuring and identifying energy consumption in any industry, they can be used handsfree, remotely without interruption to the mains power. The logger tracks even the slightest consumption in an electrical network, providing all Power and Energy measurement recording on the internal 2GB SD card, while simultaneously permitting real-time monitoring on its backlit 4 line LCD display. Recordings are time/date stamped for ease of comparing measured gains achieved before and after installation modification. Easily transfer recorded data to a PC via the free PEL data transfer software and SD card with USB adaptor (included).

Designed to fit inside most electrical cabinets thanks to its magnetic base or hook for easy mounting.

## Key Features of the PEL103 include:

Measurements and display of:

- RMS frequency, voltage and current measurements
- Voltage measurement ranges 10 to 1000V AC/DC +/- 0.2 % + 0.5 V
- . Current measurement ranges 5 mA to 10 kA AC / 50 mA to 1,4 kA DC ±0.5 %
- VA, W and var power values
- . Power Factor (PF),  $\cos \phi$ ,  $\tan \phi$  and crest factor
- Total Harmonic Distortion (THD) for currents and voltages
- DC, 50 Hz, 60 Hz and 400 Hz measurements
- . Phase rotation indication and MIN/MAX indication of all parameters
- VAh, Wh (source, load) and varh (4 guadrant) energy values, total energy
- Harmonics: up to the 50th order for currents and voltages (an essential feature to help identify problems)
  - Three phase (with or without neutral), split phase, single phase Network types include: Automatic recognition: Of the type of sensor connected Communication / Data transfer: USB, Ethernet and Bluetooth / PEL transfer PC software (included)
    - Measurements and calculation results on SD card (included) 128s/period

## PEL 103 Power and Energy logger (KIT)

Records:

Acquisition rate:

-

(created as a complete kit with following accessories)

1 x PEL103 Power and Energy Logger:

- 3 x MA193 (200 mm) flexible current clamps:
- 4 x Measurement leads and crocodile clips:
- 1 x Set of coloured rings and Inserts:

1 x 2GB SD card (internal):

Analyser with backlit LCD screen MINIFLEX MA193 flexible current sensors - 200mA to 10 kA Robust high quality test leads for frequent use/built to last For easy identification of connections and leads SD card to USB adaptor

SD card to USB adapter, USB cable, mains cable, MultiFIX mounting system, operating manual (on CD) PEL transfer PC software enabling data to be transferred to PC, all in a convenient canvas carrying bag.

type	model	description	dimensions (mm)			
		-	(H)	(W)	(D)	
PEL 103 Power and Energy logger (KIT)						
P01157151 P01157150	PEL103 <b>(KIT)</b> PEL102 <b>(KIT)</b>	portable power and energy logger/analyser as above, but without LCD display screen	256 256	125 125	37 37	
Accessories for PEL103 Power and Energy logger						
P01120434B P01120323B P01120580* P01120526B P01101959	C193 MA193-250	compact tong clamps for PEL102/3 compact tong clamps for PEL102/3 Ampflex 250 mm flexible current sensor Ampflex 450 mm flexible current sensor for reading from 5A secondary CT's	Ø20 mm Ø52 mm Ø70 mm Ø140 mm	0.005 - 7 1 - 100 200mA - 100mA - 5A ada	00A 10kA 10kA	
P01102134 P01295174* P01295476* P01102080* P01298078*		mains adaptor for self powering PEL from su mains power cable - (2P EUR) spare measurement leads (3m) with croco ID rings and inserts (for ends of leads and canvas carrying bag for PEL analyser and	odile clips d sensors)	mains ad KIT <i>(bla</i> diff. cole	ack)	
* Items supplied with standard PEL KIT.						
Data processing software power quality & installation supervision						
Automatically recognizes the instrument connected to the PC and opens the corresponding menu, providing direct access to the configuration and saved data. Includes many predefined report templates for quick generation in compliance with applicable standards.						

Users can create personalised models to fit their requirements and add comments directly.

- Configuration of all the functions of instruments connected to a PC or via Bluetooth
- Recovery of the recorded measurement data and backup of measurement files
- Opening of saved files / processing and creation of reports (EN50160)
- Export into an Excel spreadsheet or PDF format / Database management

P01102095 DataView powerful configuration/transfer/measurement data processing software