



Busbar supports

The MRS range of busbar supports are four pole (3Ph+N) with stepped phases for easy access and termination. Ideally combined with drilled and threaded copper busbars to make up distribution terminals of any size. Insulating protection covers are available (*in one-meter lengths*) to provide protection against accidental touch of the bars. Ipk ratings are influenced by bar dimensions and the distance between supports.

Maximum operating temperature: +85°C Heat resistance: +130°C
 Insulating body material: Polyamide
 Mounting: DIN rail or chassis mount
 Standards: CEI EN 17-13/1 EN 60439

type	amps	no. bars	max bar width	description	dimensions (mm)		
					(H)	(W)	(D)

Multi-pole busbar supports

- DIN rail or chassis mount
- With mounting accessories for (*optional*) protection cover and busbar mounting

2 pole supports (1Ph+N)

supplied in pairs (2pcs)

MRS122	65A	2	12 mm	1P+N	busbar supports (2 pcs)	47	14	18
---------------	-----	---	-------	------	-------------------------	----	----	----

4 pole stepped supports (3Ph+N)

supplied in 4 pcs (2 pair per set)

160A - 4 pole busbar support

MRS416	160A	4	16 mm	3P+N	busbar supports (4 pcs)	90	25	57
---------------	------	---	-------	------	-------------------------	----	----	----

250A - 4 pole busbar support

MRS420	250A	4	20 mm	3P+N	busbar supports (4 pcs)	132	67	59
---------------	------	---	-------	------	-------------------------	-----	----	----

Terminal protection covers (for above supports)

MRC2150	screen	protection cover for busbar support MRS416	(1 meter length)
----------------	--------	---	------------------

MRC2250	screen	protection cover for busbar support MRS420	(1 meter length)
----------------	--------	---	------------------

MTB	DIN rail earthing terminal	(for connecting earth wire to DIN rail)
------------	----------------------------	---