

new



PMGB12-5



PMGB16-7B



PMGB25-18



PMGB40-32



MGM32-22



PPGA20-E-14B



PHPM20B

Cable glands (compression)

Thread: Metric
 Protection degree: IP68-10
 Material: Body: Nylon PA66 UL approved (*Flammability UL94V-2*) Seal: EPDM
 Ambient temperature: -40°C...+100°C (*instantaneous heat resistance up to 120°C*)

type	AG (mm)	thread length	compress area (mm)	colour	description
M - Metric thread cable glands (supplied with locknut)					
PMGB12-5	M12	8.5 mm	3-5.5	light grey	Metric compression gland
PMGB16-7	M16	10 mm	3-7	light grey	Metric compression gland
PMGB18-10	M18	10 mm	6-10	light grey	Metric compression gland
PMGB20-13.5	M20	10 mm	9-14	light grey	Metric compression gland
PMGB25-18	M25	12 mm	13-18	light grey	Metric compression gland
PMGB32-25	M32	12 mm	18-25	light grey	Metric compression gland
PMGB40-32	M40	15 mm	24-32	light grey	Metric compression gland
PMGB50-41	M50	15 mm	31-41	light grey	Metric compression gland
PMGB63-45	M63	18 mm	35-45	light grey	Metric compression gland
PMGB12-5B	M12	8.5 mm	3-6.5	black	Metric compression gland
PMGB16-7B	M16	10 mm	4-8	black	Metric compression gland
PMGB18-10B	M18	10 mm	6-10	black	Metric compression gland
PMGB20-13.5B	M20	10 mm	9-14	black	Metric compression gland
PMGB25-18B	M25	12 mm	13-18	black	Metric compression gland
PMGB32-25B	M32	12 mm	18-25	black	Metric compression gland
PMGB40-32B	M40	15 mm	26-31	black	Metric compression gland
PMGB50-41B	M50	15 mm	26-31	black	Metric compression gland
PMGB63-45B	M63	18 mm	35-45	black	Metric compression gland
PG - Thread cable glands (supplied with locknut)					
PPGB7-5B	12.5	8 mm	3-5.5	black	PG compression gland
PPGB9-8B	15.2	8 mm	4-8	black	PG compression gland
PPGB11-10B	18.6	10 mm	6-10	black	PG compression gland
PPGB13.5-12B	20.4	10 mm	7-12.5	black	PG compression gland
PPGB16-11B	22.5	11 mm	6-11	black	PG compression gland
PPGB19-14B	24	11 mm	8.5-14	black	PG compression gland
PPGB21-18B	28.3	12 mm	12-18	black	PG compression gland
Metal cable glands (supplied with locknut)					
Material:	Body:	Nickel plated brass			
	Seal:	Nylon PA66, EPDM rubber			
MGM8-4.5	M8	4 mm	3-4.5	nickel	metal compression gland
MGM12-6.5	M12	6.5 mm	3-6.5	nickel	metal compression gland
MGM16-8	M16	8 mm	4-8	nickel	metal compression gland
MGM18-10	M18	8 mm	5-10	nickel	metal compression gland
MGM20-12	M20	8 mm	6-12	nickel	metal compression gland
MGM22-14	M22	8 mm	10-14	nickel	metal compression gland
MGM25-16	M25	9 mm	10-16	nickel	metal compression gland
MGM32-22	M32	10 mm	15-22	nickel	metal compression gland
MGM40-30	M40	11 mm	22-30	nickel	metal compression gland
MGM50-38	M50	13 mm	32-38	nickel	metal compression gland
MGM63-44	M63	14 mm	37-44	nickel	metal compression gland
90° Degree cable glands (supplied with locknut)					
Material:	Nylon PA66 UL approved (<i>Flammability UL94V-2</i>)				
PPGA16-E-08B	M16	10 mm	4-7	black	90° compression gland
PPGA20-E-14B	M20	15 mm	9-14	black	90° compression gland
PPGA25-E-18B	M25	15 mm	13-18	black	90° compression gland
PPGA32-E-25B	M32	15 mm	18-25	black	90° compression gland
Nylon hole plugs (supplied with locknut)					
Material:	Nylon PA66 UL approved (<i>Flammability UL94V-2</i>)				
PHPM12B	M12	9.5 mm	-	black	screw-in blanking plugs
PHPM16B	M16	10 mm	-	black	screw-in blanking plugs
PHPM20B	M20	11 mm	-	black	screw-in blanking plugs
PHPM22B	M22	11 mm	-	black	screw-in blanking plugs
PHPM25B	M25	11 mm	-	black	screw-in blanking plugs
PHPM32B	M32	11 mm	-	black	screw-in blanking plugs
PHPM40B	M40	12 mm	-	black	screw-in blanking plugs
PHPM50B	M50	12 mm	-	black	screw-in blanking plugs
PHPM63B	M63	12 mm	-	black	screw-in blanking plugs