



Crimped ferrule



Ferrules / wire end sleeves (Insulated)

- Material: Tin-plated copper (min. thickness 3µ) / polypropylene collar
- CSA certified (certificate 2110332)
- DIN 46228 part 4, CSA C22.2 No. 65-93, 188-M1983

type	wire size mm ²	colour	dimensions (mm)						pack qty
			L1	L2 ¹⁾	D1	S1	D2	D3	

Wire end sleeves with insulating collar

- Supplied in mini bags on a strip (10 x 100 pcs). bags can be torn from strip individually

005606	0.50	white	14.0	8.0	1.1	0.15	2.4	-	0.30	100
005644	0.75	blue	14.0	8.0	1.3	0.15	2.7	-	0.30	100
005718*	1.0	red	14.0	8.0	1.5	0.15	3.3	-	0.30	100
005738*	1.0	red	16.0	10.0	1.5	0.15	3.3	-	0.30	100
005765*	1.5	black	14.0	8.0	1.8	0.15	3.7	-	0.30	100
005791*	1.5	black	16.0	10.0	1.8	0.15	3.7	-	0.30	100
005808	2.5	grey	15.0	8.0	2.3	0.15	4.1	-	0.30	100
005829	2.5	grey	17.0	10.0	2.3	0.15	4.1	-	0.30	100
005831*	2.5	grey	18.0	10.0	2.3	0.15	4.7	-	0.30	100
005851	4.0	orange	18.0	10.0	2.9	0.20	4.7	-	0.30	100
007739*	4.0	grey	18.0	10.0	2.9	0.20	6.1	-	0.30	100
005871	6.0	green	20.0	12.0	3.6	0.20	6.1	-	0.30	100
005896	10.0	brown	21.0	12.0	4.6	0.20	7.4	-	0.40	100
005917	16.0	white	23.0	12.0	6.0	0.20	8.6	-	0.50	100
005919*	16.0	white	23.0	12.0	6.0	0.20	9.4	-	0.50	100
005950	25.0	black	29.0	16.0	7.5	0.20	10.9	-	0.50	50
005968	35.0	red	30.0	16.0	8.5	0.20	12.3	-	0.50	50
005980	50.0	blue	36.0	20.0	10.5	0.30	14.8	-	0.60	50
005988	70.0	yellow	37.0	20.0	12.7	0.40	15.8	-	0.60	25
005990	95.0	red	44.0	25.0	14.7	0.40	17.7	-	0.60	25
005915	120.0	blue	48.0	27.0	16.7	0.50	20.7	-	0.70	25
005916	150.0	yellow	58.0	32.0	18.7	0.50	22.6	-	1.00	25

* Broader collar to accommodate wires with thicker insulation

Twin wire end sleeves with insulating collar (accepts two cables)

type	wire size (mm ²)	colour	dimensions (mm)						pack qty
			L1	L2 ¹⁾	D1	S1	D2	A	

- Accepts two wires into one insulated end sleeve
- Supplied in mini bags on a strip (10 x 100 pcs). bags can be torn from strip individually

005613	2 x 0.5	white	15.0	8.0	1.5	0.15	2.4	4.6	0.30	100
005653	2 x 0.75	blue	15.0	8.0	1.8	0.15	2.7	5.4	0.30	100
005722	2 x 1.0	red	15.0	8.0	2.1	0.15	3.3	5.3	0.30	100
005740	2 x 1.0	red	17.0	10.0	2.1	0.15	3.3	5.3	0.30	100
005770	2 x 1.5	black	16.0	8.0	2.3	0.15	3.5	6.5	0.30	100
005794	2 x 1.5	black	20.0	12.0	2.3	0.15	3.5	6.5	0.30	100
005816	2 x 2.5	grey	19.0	10.0	2.9	0.20	4.1	7.7	0.40	100
005853	2 x 4.0	orange	23.0	12.0	3.8	0.20	4.9	8.7	0.40	100
005873	2 x 6.0	green	25.0	14.0	4.9	0.20	6.1	9.9	0.40	100
005898	2 x 10.0	brown	26.0	14.0	6.5	0.20	7.1	12.9	0.50	100
005921	2 x 16.0	white	31.0	16.0	8.5	0.20	9.8	16.8	0.60	50

Wire end sleeves with insulating collar supplied in belt strips

Wire end sleeves in belt form (K reels), for use in automatic cable preparation machines (see page M-4)
Reel/cassette simply clips onto machines (500/1000 terminals per reel)

- Tape mounted supplied in type K box dispenser (box size = 150 x 150 x 18 mm)

type	wire size (mm ²)	colour	dimensions (mm)						reel qty
			L1	L2 ¹⁾	D1	S1	D2	centre	

005611	0.50	white	14.5	8.0	1.1	0.15	2.6	3.5	0.25	1000
005649	0.75	blue	14.5	8.0	1.3	0.15	2.7	3.6	0.25	1000
005720	1.0	red	14.5	8.0	1.5	0.15	3.0	3.9	0.30	1000
005767	1.5	black	14.5	8.0	1.8	0.15	3.2	4.2	0.30	1000
005813	2.5	grey	14.5	8.0	2.3	0.15	4.1	5.0	0.30	500

¹⁾ Other lengths available on request



005649