

	type	colour	wire size mm ²	description	dimensions (mm)			pack qty	
					d2	B	L		
Flat-blade terminal									
	BT1-10V	red	0.5 - 1.5	insulated flat blade lug	2.4	10.7	20.7	100	
	BT1-14V	red	0.5 - 1.5	insulated flat blade lug	3	14	24	100	
	BT1-18V	red	0.5 - 1.5	insulated flat blade lug	2.4	18	28	100	
	BT2-10V	blue	1.5 - 2.5	insulated flat blade lug	2.4	10.7	20.7	100	
	BT2-13V	blue	1.5 - 2.5	insulated flat blade lug	2.4	13	23	100	
	BT2-18V	blue	1.5 - 2.5	insulated flat blade lug	2.4	18	28	100	
	BT5-10V	yellow	4.0 - 6.0	insulated flat blade lug	2.8	10	22.5	100	
	BT5-18V	yellow	4.0 - 6.0	insulated flat blade lug	3	18	30.5	100	
	Hook-blade terminal								
		LB1-3V	red	0.5 - 1.5	insulated hook blade lug	3.0	18.0	28.0	100
LB1-4.6V		red	0.5 - 1.5	insulated hook blade lug	4.6	18.0	28.0	100	
LB2-3V		blue	1.5 - 2.5	insulated hook blade lug	3.0	18.0	28.0	100	
LB2-4.6V		blue	1.5 - 2.5	insulated hook blade lug	4.6	18.0	28.0	100	
LB5-3V		yellow	4.0 - 6.0	insulated hook blade lug	3.0	17.5	30.0	100	
LB5-4.6V		yellow	4.0 - 6.0	insulated hook blade lug	4.6	17.5	30.0	100	
Female disconnect terminals "push-on"									
		F1-2.8V/5	red	0.5 - 1.5	female disconnect	2.8	3.2	18.5	100
	F1-2.8VD/5*	red	0.5 - 1.5	female disconnect	2.8	3.2	18.5	100	
	F1-4.8V/5	red	0.5 - 1.5	female disconnect	4.8	5.0	19.0	100	
	F1-4.8VD/5*	red	0.5 - 1.5	female disconnect	4.8	5.0	19.0	100	
	F1-6.4V	red	0.5 - 1.5	female disconnect	6.4	6.6	21.0	100	
	F1-6.4VF	red	0.5 - 1.5	fully insulated disconnect	6.4	6.6	22.0	100	
	F1-6.4VD*	red	0.5 - 1.5	female disconnect	6.4	6.6	21.0	100	
	F1-6.4VQD*	red	0.5 - 1.5	fully insulated disconnect	6.4	6.6	21.5	100	
	F2-2.8VD/5*	blue	1.5 - 2.5	female disconnect	2.8	3.2	18.5	100	
	F2-4.8V/5	blue	1.5 - 2.5	female disconnect	4.8	5.0	19.0	100	
	F2-4.8VD/5*	blue	1.5 - 2.5	female disconnect	4.8	5.0	19.0	100	
	F2-6.4V	blue	1.5 - 2.5	female disconnect	6.4	6.6	21.0	100	
	F2-6.4VF	blue	1.5 - 2.5	fully insulated disconnect	6.4	6.6	22.0	100	
	F2-6.4VD*	blue	1.5 - 2.5	female disconnect	6.4	6.6	21.0	100	
	F2-6.4VQD*	blue	1.5 - 2.5	fully insulated disconnect	6.4	6.6	21.5	100	
	F2-8V	blue	1.5 - 2.5	female disconnect	8.0	8.4	24.0	100	
	F2-8VD*	blue	1.5 - 2.5	female disconnect	8.0	8.4	24.0	100	
	F5-6.4V	yellow	4.0 - 6.0	female disconnect	6.4	6.6	23.5	100	
	F5-6.4VD*	yellow	4.0 - 6.0	female disconnect	6.4	6.6	23.5	100	
	F5-6.4VQD*	yellow	4.0 - 6.0	fully insulated disconnect	6.4	6.6	24.5	100	
F5-9.5V	yellow	4.0 - 6.0	female disconnect	9.5	9.9	28.5	100		
F5-9.5VD*	yellow	4.0 - 6.0	female disconnect	9.5	9.9	28.5	100		
* Twin-grip crimp ■ Square entry / twin-grip / fully insulated									
Male disconnect terminals "push-on"									
	M1-2.8V/5	red	0.5 - 1.5	male disconnect	—	2.8	19.2	100	
	M1-2.8VD/5*	red	0.5 - 1.5	male disconnect	—	2.8	19.2	100	
	M1-4.8V/5	red	0.5 - 1.5	male disconnect	—	4.8	19.2	100	
	M1-4.8VD/5*	red	0.5 - 1.5	male disconnect	—	4.8	19.2	100	
	M1-6.4V	red	0.5 - 1.5	male disconnect	—	6.4	21.2	100	
	M1-6.4VD*	red	0.5 - 1.5	male disconnect	—	6.4	21.2	100	
	M2-2.8V/5	blue	1.5 - 2.5	male disconnect	—	2.8	19.2	100	
	M2-2.8VD/5*	blue	1.5 - 2.5	male disconnect	—	2.8	19.2	100	
	M2-4.8V/5	blue	1.5 - 2.5	male disconnect	—	4.8	19.2	100	
	M2-4.8VD/5*	blue	1.5 - 2.5	male disconnect	—	4.8	19.2	100	
	M2-6.4V	blue	1.5 - 2.5	male disconnect	—	4.8	21.2	100	
	M2-6.4VD*	blue	1.5 - 2.5	male disconnect	—	4.8	21.2	100	
	M5-6.4V	yellow	4.0 - 6.0	male disconnect	—	6.4	23.2	100	
	M5-6.4VD*	yellow	4.0 - 6.0	male disconnect	—	6.4	23.7	100	
	* Twin-grip crimp								