new

Cable ties (stainless steel)

For use in critical applications where strength, corrosion, radiation, vibration and temperature extremes are a factor. Unique ball locking mechanism permits simple, rapid installation and secure locking in any position. High tensile strength, non flammability, UV-resistant, high resistance to acids and corrosion for a strong durable solution to bundling and mechanical fastening in harsh environments.

• Self-locking head design speeds installation and locks at any length along the tie body
• Smooth surface, rounded edges assure cable protection and worker safety

type	length (mm)	wide (mm)	thick (mm)	AISI	bundle dia max.(mm)	description	
AISI 304 stainless steel					*for general purpose applications*		*per (100)*
Working temperature:		-60°C – +550°C					
Metallic band and buckle							
SST4/15-04	150	4.6	0.25	304	37	stainless steel cable ties	
SST4/25-04	250	4.6	0.25	304	63	stainless steel cable ties	
SST4/35-04	350	4.6	0.25	304	89	stainless steel cable ties	
SST4/45-04	450	4.6	0.25	304	115	stainless steel cable ties	
SST4/55-04	550	4.6	0.25	304	141	stainless steel cable ties	
SST7/25-04	250	7.9	0.25	304	63	stainless steel cable ties	
SST7/45-04	450	7.9	0.25	304	115	stainless steel cable ties	
SST7/60-04	600	7.9	0.25	304	154	stainless steel cable ties	
SST7/80-04	800	7.9	0.25	304	193	stainless steel cable ties	
AISI 316 stainless steel - Epoxy coated					*for extra corrosive environments*		*per (100)*

• Black band with metallic buckle
• Coated band with non-toxic, Halogen free polyester coating
• Provides additional edge protection, prevents corrosion between dissimilar materials

type	length (mm)	wide (mm)	thick (mm)	AISI	bundle dia max.(mm)	description
SSTP4/20-16	200	4.6	0.36	316	50	stainless steel cable ties
SSTP4/30-16	300	4.6	0.36	316	76	stainless steel cable ties
SSTP4/40-16	400	4.6	0.36	316	102	stainless steel cable ties
SSTP4/50-16	500	4.6	0.36	316	128	stainless steel cable ties
SSTP7/30-16	300	7.9	0.36	316	76	stainless steel cable ties
SSTP7/40-16	400	7.9	0.36	316	102	stainless steel cable ties
SSTP7/60-16	600	7.9	0.36	316	154	stainless steel cable ties
SSTP7/80-16	800	7.9	0.36	316	193	stainless steel cable ties

Marking tags - stainless steel   *(cable tie max. width 4.6 mm)*   *per (100)*

Stainless steel tie-on tags for permanent identification of cables, conduits, pipes in arduous applications where high resistance to aggressive environments is essential.

AISI 304 stainless steel

type	length	wide	thick	AISI		description
SSM1089-04	89	9.5	0.40	304	–	stainless steel marking tags
SSM1989-04	89	19	0.40	304	–	stainless steel marking tags

AISI 316 stainless steel

type	length	wide	thick	AISI		description
SSM1089-16	89	9.5	0.40	316	–	stainless steel marking tags
SSM1989-16	89	19	0.40	316	–	stainless steel marking tags

Laser engraved stainless steel tags *(each)*

Custom laser marking of tags and cable ties. Upper/lower case characters, detailed marking, text and graphics, high quality, crisp, clean and permanent.

• Once laser engraved the inscription remains with the product for life

type	length	wide	thick	AISI	description
SSM1089-04/PS*	89	9.5	0.40	304	custom engraved marking tags
SSM1989-04/PS❖	89	19	0.40	304	custom engraved marking tags
SSM1089-16/PS*	89	9.5	0.40	316	custom engraved marking tags
SSM1989-16/PS❖	89	19	0.40	316	custom engraved marking tags

*** Print area: L:79 x W:8.5 – ❖ Print area: L:79 x W:18**
Please provide detailed information on required laser engraving of tags when ordering.

Accessories *(cable tie gun)*

• Tensioning tool *(with auto cut)* for all above stainless steel cable ties
• Adjustable tension value - *(4 settings)*

HS-600   tensioning and cutting tool for 4.6 and 7.9 mm SS cable ties

SST7/45-04

SSTP7/40-16

SSM1089-04

SSM1089-16

Print area

A62350/12235-ELEC 21O5/663A

SSM1089-04/PS

HS-600