



6531...



6531...



6682...



6622...PCB

65 series**High power relays**

(43.3 x 32.2 x 36.6 mm)

- AC and DC coil voltages
- Flange mount with faston 250 (6.3 x 0.5 mm) termination
- ATEX compliant options (*available on request*)
- Reinforced insulation between coil and contacts to EN60335-1

type	current	description	contact configuration	coil voltage
20A 1 NO + 1 NC				
653180120000	20A	plug-in industrial power relay	1 NO + 1 NC	12 VAC
653180240000	20A	plug-in industrial power relay	1 NO + 1 NC	24 VAC
653180480000	20A	plug-in industrial power relay	1 NO + 1 NC	48 VAC
653181100000	20A	plug-in industrial power relay	1 NO + 1 NC	110 VAC
653182400000	20A	plug-in industrial power relay	1 NO + 1 NC	240 VAC
653184000000	20A	plug-in industrial power relay	1 NO + 1 NC	400 VAC
653190120000	20A	plug-in industrial power relay	1 NO + 1 NC	12 VDC
653190240000	20A	plug-in industrial power relay	1 NO + 1 NC	24 VDC
653190480000	20A	plug-in industrial power relay	1 NO + 1 NC	48 VDC
653191100000	20A	plug-in industrial power relay	1 NO + 1 NC	110 VDC
653192200000	20A	plug-in industrial power relay	1 NO + 1 NC	220 VDC
30A 1 NO				
• ≥ 3 mm contact gap				
653180120300	30A	plug-in industrial power relay	1 NO	12 VAC
653180240300	30A	plug-in industrial power relay	1 NO	24 VAC
653180480300	30A	plug-in industrial power relay	1 NO	48 VAC
653181100300	30A	plug-in industrial power relay	1 NO	110 VAC
653182400300	30A	plug-in industrial power relay	1 NO	240 VAC
653184000300	30A	plug-in industrial power relay	1 NO	400 VAC
653190120300	30A	plug-in industrial power relay	1 NO	12 VDC
653190240300	30A	plug-in industrial power relay	1 NO	24 VDC
653190480300	30A	plug-in industrial power relay	1 NO	48 VDC
653191100300	30A	plug-in industrial power relay	1 NO	110 VDC
653192200300	30A	plug-in industrial power relay	1 NO	220 VDC
Other configurations:				
PCB mount terminals: replace 3rd digit 65 (3) with (6) (e.g. 65 6 180120000)				
Accessories for 65 series relays				
06507		DIN rail mounting frame	<i>(terminals facing forward)</i>	
06508		DIN rail mounting frame	<i>(terminals facing down)</i>	

66 series**High power 2 pole relays**

(31 x 51.5 x 33.5 mm)

- AC and DC coil voltages
- Faston 250 (6.3 x 0.8 mm) termination
- 8 mm, 6kV (1.2/50 µs) isolation, coil-contacts
- 2 pole changeover contacts 30A NO - 10A NC
- Reinforced insulation between coil and contacts to EN60335-1

30A 2 changeover

668280120000	30A	plug-in industrial power relay	2 changeover	12 VAC
668280240000	30A	plug-in industrial power relay	2 changeover	24 VAC
668281100000	30A	plug-in industrial power relay	2 changeover	110 VAC
668282400000	30A	plug-in industrial power relay	2 changeover	240 VAC
668290120000	30A	plug-in industrial power relay	2 changeover	12 VDC
668290240000	30A	plug-in industrial power relay	2 changeover	24 VDC
668291100000	30A	plug-in industrial power relay	2 changeover	110 VDC

PCB termination: replace 3rd digit 66 (8) with (2) (e.g. 66**2**280120000)**Accessories for 66 series relays**

06607	DIN rail mounting frame	<i>(terminals facing forward)</i>	
--------------	-------------------------	-----------------------------------	--