



P44LM1



P44RPM1



P49MFT1



P49VM

48 x 48 panel mount - signal indicators/monitors (4 - 20mA) loop

Displays and/or monitors transducer generated signals with outputs 4 - 20mA as real world values from -999 to 9999 for indicating voltage, current, temperature, pressure etc. and displaying in real values.

type	supply voltage*	range	relays	with 4-20mA	description
Loop indicator					
P44LM1-240A	240 VAC	0/4 - 20mA	1	-	loop indicator
P44LM1-P-240A	240 VAC	0/4 - 20mA	1	24 VDC PS	loop indicator
P44LM1-T-240A	240 VAC	0/4 - 20mA	1	yes	loop indicator
P44LM2-240A	240 VAC	0/4 - 20mA	2	-	loop indicator
P44LM2-P-240A	240 VAC	0/4 - 20mA	2	24 VDC PS	loop indicator
P44LM2-P-024D	24 VDC	0/4 - 20mA	2	24 VDC PS	loop indicator
P44LM2-T-240A	240 VAC	0/4 - 20mA	2	yes	loop indicator

Note: 0-10V re-transmit output available on request.

Signal indicator / monitors – 0-10V input

Displays and/or monitors transducer generated signals with outputs 0 - 10V as real world values from -999 to 9999 for indicating voltage, current, temperature, pressure etc. and displaying in real values.

P44SM1-10-240A	240 VAC	1 - 10V*	1	-	signal monitor
----------------	---------	----------	---	---	----------------

* Available with a 0-5V or 10K potentiometer input on request

RPM / pulses per hour

Displays and/or monitors speed (RPM) relay remains energised while monitored speed is within pre-set parameters NO-NPN proxi, (PNP available on request).

P44RPM1-240A	240 VAC	0 - 9999	1	-	RPM monitor
P44RPM2-240A	240 VAC	0 - 9999	2	-	RPM monitor

48 x 96 – Digital timing devices and pre-select counter

48 x 96 mm panel mounting digital timing, counting, control and monitoring devices are available in a compact housing design. Offer many innovative features such as various relay output options as well as "re-tx" (re-transmit) function offering an additional 4 - 20 mA output with specific monitoring devices.

- Feature ability to continue from where left off in the event of a power loss during timing.

P49MFT1-240A	240 VAC	1sec - 9999 hrs	1	-	multi-function timer
P49MFT1-024AD	24V AC/DC	1sec - 9999 hrs	1	-	multi-function timer
P49ACT1-240A	240 VAC	1sec - 100 hrs	1	-	accumulation timer
P49CNT1-240A	240 VAC	4 digit mode	1	-	counter / frequency monitor
P49CNT1-024AD	24V AC/DC	4 digit mode	1	-	counter / frequency monitor
P49CWT1-240A	240 VAC	0 - 100min or hrs	1	-	digital clockwork timer

Voltage indicator / monitor

- Displays and/or monitors true RMS single or three phase supply voltages

P49VM10-240A	240 VAC	0 - 300V*	1	-	single phase voltage monitor
--------------	---------	-----------	---	---	------------------------------

0 - 10V re-transmit available on request

P49VM31N-400A	400 VAC	0 - 500V	1	-	3 ph voltage & frequency indicator
P49VM32N-400A	400 VAC	0 - 500V	2	-	3 ph voltage & frequency indicator

(N) software selectable neutral monitoring as well.

P49VMD2-240A	240 VAC	0 - 150V*	2	-	DC voltage indicator
--------------	---------	-----------	---	---	----------------------

0 - 10V re-transmit available on request

* Other voltage options available on request.